

# Status of The 3rd Test Beam Experiment @ELPH in Tohoku Univ.

Only 31 days left

G. Nukazuka (RBRC)



# Purpose

## Determination of the detection efficiency

Past beam experiments showed 96% efficiency. But it must be almost 100%.

Mismatch of the BCO phase and beam can explain the reason.

We are ready to take the external trigger information and BCO phase with the CAMAC system.

Cosmic-ray measurements with the CAMAC system showed 98% efficiency. More improvements are not easy since statistics are limited, optimization of the geometry is so delicate.


→ We need test beam measurements with the CAMAC system to proof ~100% efficiency

## Beam measurements with the production ladders

We need to see performance of the production ladder with a beam.




## Beam measurements with the latest bus extenders and the co-axial conversion cables

The design of the bus extender was finalized. We will get the co-axial conversion cable some months later. So they should be tested with a beam.



# Research Center for **EL**ectron **PH**oton Science (ELPH)

[NIM A 694 \(2012\) 348](#)



# Beam features@ELPH GeV- $\gamma$ area

## Electron test beam


Beam	Beam line	Maximum beam energy
Positron / Electron	$\pm 30$ deg	~840 MeV
Positron	-23 deg	~1000 MeV

[HomePage](#)


## Tagged gamma-ray beam

Beam line	Energy Range (R <sub>int</sub> Energy: 1.3 GeV)	# of Bins	Intensity	Duty
BST-Tagger-I	0.8 ~ 1.26 GeV	160	TBC	~60% (NKS2)
BST-Tagger-II	0.9 ~ 1.25 GeV	116	TBC	~50% (FOREST)


[HomePage](#)



Current for the magnet (A)




Electron beam energy (MeV)



Gamma-ray energy (MeV)

# Tentative Member



**NWU**  
Staff: T. Hachiya  
Master std.: Mika, Miu, Yumika, and Runa  
Bachelor std.: Yuka, Mai, and Misaki

**JAEA**  
Staff: Shoichi


**Rikkyo Univ.**  
Master std.: Hikaru  
Bachelor std.: Yusuke & Genta

**RIKEN**  
Staff: Yasuyuki, and Itaru  
(+Genki???)

Under current self quarantine policy for people from overseas, it's hard to come. Recently I heard the rumor that the policy may be loosen. No official statements were made for the moment.  
Cheng-Wei?


# Dark box (BNL)

Material : Dupont [Delrin](#)® (polyacetal, 1.42 g/cm<sup>3</sup>)




Volume= 6.54 in x 25.0 in x 6.54 in

Weight= 33 pounds = 15 kg



The dark box was already produced.  
It should depart from BNL this week.


# The frame structure for the dark box and the ROC (Genki)







The basic design was established as already shown last week.

Some minor updates were made:

- thicker frames to stand the weight of the dark box
- additional frames for PMT fixations
- width flexibility to fit the stage below this structure




# The frame structure for the dark box and the ROC (Genki)



trigger scintillators

# The setup



Production targets

Au 20  $\mu$ m

W 200  $\mu$ m

Cu 8mm

etc.



# The setup




$e^+/e^-$  beam line  
up to 1 GeV/c

PC



NIM  
CAMAC  
crates




chiller

Power supplies  
come here (?)

# The setup

beam height:  
1610 mm  $\pm$  10 mm




electrically  
adjustable

by hand

floor

# Migration to Windows10 (Hikaru, Genki, & Itaru)

Since we need to operate the testbench in the experimental area in underground floor from the control room in the ground floor, remote access to the DAQ PC is mandatory.  
→ Migration to Windows10 needed.



↑ ground floor:  
control room



↑ underground:  
experimental area



Hikaru's report shown in INTT JP meeting.


Some processes were needed:

- FTD2XX.dll changed for 64 bit OS
- readDAQ.exe compiled again


Calibration data were taken successfully.

Once migration is completed, codes will be distributed via GitHub, and Hikaru will report about it.

# Testbench operation with the new CAMAC DAQ system (Yumika & Yuka)




- **Detection efficiency as a function of BCO phase** is the main purpose of this experiment
- **The new testbench DAQ** made by Genki, which consists of the standard testbench DAQ and new CAMAC DAQ, demonstrated the measurement with cosmic ray in March/2021.
- **Yumika and Yuka succeeds reconstruction of the circuit, maintenance, tuning, and optimization. Most parts of the NIM + CAMAC circuit were made.** She is working for remains, which is for the BCO phase measurement. (n.b. Yumika is also working for the ladder quality assurance)



## PMT漏電問題

ハイボルトケーブルとシンチレータの接続部分を曲げたり締めたり引っぱったりしたが、ハイボルトの電流値に変化はなく、漏電の原因は見つけれなかった。




シンチAのハイボルトの電流値 シンチBのハイボルトの電流値 シンチCのハイボルトの電流値

Yuka's first report about light leak of the scintillators and investigation for leakage from PMTs' HV line (not confirmed, but Genki got electrical shock before...)

# Multi-ladder operation (Yumika & Yuka)

## ビームテスト準備:複数ラダーの読み出し確認

- 理研から3本目の電源ケーブルが届いたので、3つのラダーを接続してキャリブレーションテストを行った
- 使用したポートはA2,C1,C3



2021/11/4



INTTJPMT


4

Multi-ladder operations were demonstrated in calibration mode successfully (no bias since not enough cables available at that time).


## Conversion cables and bus extenders

	RIKEN	NWU
short conv. cable	1	1
long conv. cable	1	2
bas extender	many	5, 6


RIKEN & NWU have enough bias cables. The conversion cables are not enough.



7



8




9

Yumika's report at INTT JP meeting

# Checking macro for the multi-ladder operation (Genki)

The checking macro (check\_chip\_prototypeMaximum6.c) was upgraded to work for data from multi-ladder operation (check\_chip\_prototypeMaximum7.c). It was announced in the mailing list and found in our GitHub repository:

<https://github.com/sPHENIX-Collaboration/INTT>



The screenshot shows a GitHub repository page for 'INTT / general\_codes /'. A commit by GenkiNukazuka is highlighted, titled 'A new version 7 of the checking macro for our testbench "check\_chip\_...". The commit message for this version is 'A new version 7 of the checking macro for our testbench "check\_chip\_...". The commit history table below shows several other commits, including updates to README.md and various C files like check\_chip\_prototypeMaximum6.c and check\_chip\_prototypeMaximum7.c.

File	Commit Message	Time
..		
functions	A new version 7 of the checking macro for our testbench "check_chip_...	yesterday
genki	codes in my local environment migrated.	2 months ago
morita	M. Morita's macros moved to the new directory "morita", unknown ROOT ...	2 months ago
obsolete	old files moved to the obsolete dir. old ROOT files removed (still ke...	2 months ago
shibata	old check_chip macros moved to the new directory "obsolete", M. Shiba...	2 months ago
README.md	Create README.md	2 months ago
check_chip_prototypeMaximum6.c	the latest version of check_chip_prototypeMaximum added. It should al...	last month
check_chip_prototypeMaximum7.c	A new version 7 of the checking macro for our testbench "check_chip_...	yesterday
check_rawchip.C	codes in my local environment migrated.	2 months ago
fileopen.C	codes in my local environment migrated.	2 months ago
fphx_raw2root.C	codes in my local environment migrated.	2 months ago
plot_chip.C	codes in my local environment migrated.	2 months ago
plot_readtree2.C	codes in my local environment migrated.	2 months ago

**README.md**

## general codes

General codes for the INTT analysis are here. Many old macros are stored in the obsolete directory.

Previous version  

```
int check_chip_prototypeMaximum6(  
    string fname, int usemod,  
    string mode, string cut  
)
```




Latest version  

```
int check_chip_prototypeMaximum7(  
    string fname, string usemod,  
    string mode, string cut  
)
```

Module IDs to be analyzed are given as a string. Commas and spaces can be used as separators.

The Nevis GUI in the Windows10 PC at RIKEN was also modified to use the latest checking macro. Updates on the GUI will be committed to the GitHub repository as well

# Geant4 simulation, and data analysis (Genki, Miu, Cheng-Wei, & Yuka)



MC data → Cheng-Wei's conversion codes

data as format as those from the testbench

**(online)  
Analysis**

Geometry was almost done.  
The codes are ready to use:  
[https://github.com/sPHENIX-Collaboration/INTT/tree/main/Testbeam\\_G4\\_code](https://github.com/sPHENIX-Collaboration/INTT/tree/main/Testbeam_G4_code)

Data from experiment  
(31 days later)



# Geant4 simulation, and data analysis (Genki, Miu, Cheng-Wei, Yuka, & Genta)

## Analysis

- Online analysis (checking macro): done
- Online analysis (tracking?): who?
- Online analysis (something else?): ?
- Detection efficiency: Miu (as a part of her Master thesis), Genki (this is my proposal)
- ADC distribution (perpendicular beam, tilted beam): Yuka, Genta
- Study to have inputs to the sPHENIX simulation
  - charge diffusion between strips: ?
  - acceptance edge effects: ?
  - track angle dependence: ? (Yuka & Genta???)
- Performance check for the setup with bus extenders: the checking macro does enough?
- more topics?

Task	Sub-tasks	Been Done	Left To Do/Notes	Resolution
Geant4	Detector component	Done		
Genki N. Kazuka	Ladders	not yet	Will be implemented once the design is settled (soon)	
	the inner and the outer skins	not yet	Will be implemented once the design is settled (soon)	
	Support structure (support pipe)	effective model	it should be enough	
	Bus extender	not yet	Will be implemented once the design is settled (soon)	
	Support structure	not yet	Will be implemented once the design is settled (soon)	
	Cabling	not yet	To be implemented for the process may not be negligible	
	Anything else?			
(mis) Misalignment	Ladder level			
?	w/ other data			
x-Calibrations	beam test data	To be analyzed	Will be implemented after December 2021 beam test	
Rikkyo Univ. & NWU	adc	To be analyzed	Will be implemented after December 2021 beam test	
	charge diffusion between strips	To be analyzed	Will be implemented after December 2021 beam test	
	acceptance edge effects	To be analyzed	Will be implemented after December 2021 beam test	
	track angle dependence	To be analyzed	Will be implemented after December 2021 beam test	
Dead/noisy maps	cosmic data w/ barrel		Can be started from lake mapping. To be updated after barrel assembly	
Purdue Univ.				
Monitor stability	cosmic data w/ barrel	Studied CMS silicon online monitor	Learn schematic framework for sPHENIX and start developing the monitor for cosmic ray data taking of the assembled barrel in Spring, 2022.	
Purdue Univ.				
Relevant runs for ALPv0	Time for each step			
	No. events needed			
	Initial 1-x calibrations			
	Calibs. filesize			
	Estimated frequency			

[https://docs.google.com/spreadsheets/d/1PLKegPAMxUJHRuPtY2yB\\_B-sZHPz8cDxUHkBgDfO4Zg/edit#gid=1908115135](https://docs.google.com/spreadsheets/d/1PLKegPAMxUJHRuPtY2yB_B-sZHPz8cDxUHkBgDfO4Zg/edit#gid=1908115135)  
[https://indico.bnl.gov/event/10538/contributions/56794/attachments/38045/62692/211102\\_CalibrationSoftware.pdf](https://indico.bnl.gov/event/10538/contributions/56794/attachments/38045/62692/211102_CalibrationSoftware.pdf)

# Data management (Genki, Yusuke, Genta, & Yuka)

Experiment data, documents, etc. are shared with [Google Drive](#). A new google account “intt.sphenix” was made for the management.


You can see the shared materials: [Google Drive](#).

If you let me know your google account, I'll invite you for the sharing.

→ Dynamical data sync to your local PC possible. The data sync test with our bachelor tests already done.

Data conservation for long term should be done at servers in BNL.

Information will be summarized in [the wiki page](#).



# Schedule

2021後期ビームタイム

加速器メンテナンス A部運転

第二実験室(NKS) GeV- $\gamma$ 実験室

同時運転不可 本体室

2021/9/1 更新

2021 10月		2021 11月		2021 12月		2022 1月		2022 2月		2022 3月				
1金	we are here	1月	屋 金田(2982)	1水		1土	冬期休業	1火	Bachelor&Master defense season at Rikkyo	1火	Bachelor defense season at NWU			
2土		2火		中瀬(2989)	2木			2水		2水				
3日		3水			3金	夜 永尾(2981) 共同研究H		3月		3木		3木		
4月	RIPF-U	4木	屋 永尾(2981)	4土	preparation	4火		4金		4金				
5火	菊永(2947)	5金	屋 永尾(2981)	5日		全 永尾(2981)		5水	5土	5土				
6水	屋 末原(2975)	6土		6木				6木	6日	6日				
7木	屋 末原(2975)	7日		7火	屋 本多(2973)	7金	予備日	7月	屋 白鳥(2976)	RI候補日	7月	RIPF-K		
8金	屋 末原(2975)	8月		8水	屋 本多(2973)	8土		8火	屋 白鳥(2976)	菊永(2947)	8火	夜 永尾(2981)	菊永(2947)	
9土		9火		9木	屋 本多(2973)	9日		9水	屋 白鳥(2976)	RI候補日	9水	全 永尾(2981)		
10日		10水		10金	屋 本多(2973)	10月		10木		RI候補日	10木	全 永尾(2981)		
11月		11木	屋 蔵満(2988)	11土		11火		11金	Master defense season at NWU	11金		後藤(2967)		
12火	共同研究H	12金	屋 蔵満(2988)	12日		12水		12土		長谷川(2985)	12土			
13水	後藤(2967)	13土		13月		13木		13日		RIPF-U	13日			
14木	屋 金田(2982)	14日		14火	屋 佐藤(2980)	14金		14月		菊永(2947)	14月		A部予約	
15金		15月		15水	屋 佐藤(2980)	15土	RIKEN APR deadline around here	15火		15火	菊永(2946)	15火		
16土		16火	屋 本多(2973)	16木	屋 佐藤(2980)	16日		16水		RI候補日	16水		RI候補日	JPS annual meeting
17日		17水	屋 本多(2973)	17金		17月		17木		RI候補日	17木		RI候補日	
18月		18木	屋 本多(2973)	18土		18火		18金		豊嶋(2987)	18金		豊嶋(2987)	
19火	施設見学	19金	屋 本多(2973)	19日		19水		19土		19土				
20水	屋 中村(2977)	20土		20月	屋 青木(2974)	RI候補日	20木	屋 大西(2979)	秋山(2986)	20日				
21木	屋 中村(2977)	21日		21火	屋 青木(2974)	RI候補日	21金	屋 大西(2979)	RI候補日	21月	屋 本多(2973)			
22金	屋 中村(2977)	22月		22水	屋 青木(2974)	菊永(2947)	22土			22火	屋 本多(2973)	菊永(2946)		
23土		23火		23木	屋 青木(2974)	秋山(2986)	23日			23水	屋 本多(2973)	RIPF-K		
24日		24水		24金		後藤(2967)	24月		RIPF-F	24木	屋 本多(2973)	菊永(2947)		
25月		25木		25土			25火	屋 糠塚(2984)	RI候補日	25金	屋 本多(2973)	RI候補日		
26火	屋 山田(2972)	26金	屋 永尾(2981)	26日			26水	屋 糠塚(2984)	大浦(2968)	26土				
27水	屋 山田(2972)	27土		27月	予備日		27木	屋 糠塚(2984)	RI候補日	27日				
28木		28日		28火	冬期休業		28金	屋 糠塚(2984)	RI候補日	28月				
29金		29月	屋 大西(2963)	29水				29土			29火			予備日
30土		30火	屋 大西(2963)	30木				30日			30水			
31日				31金			31月	予備日		31木				

October

November

December



January

February

March

**backup**

# ROC fixation




六角ナット1種 ステンレス  
 六角ナット1種 ステンレス ★★★★★ (4件の商品レビュー)  
 一般的な六角ナットです。  
 ステンレス(SUS304)材質を使用しており、耐食性があります。  
 より購入しやすい入数にしました。

Nut  
 M3  
 2.4 mm thick



六角穴付ボルト(ステンレス) 全ねじ ★★★★★ (229件の商品レビュー)  
 六角レンチで締めつけられるので機械組立に最適。  
 ねじ込み場所が狭い所にも使用できます。

Screw (Hex socket head)  
 M3  
 30 mm thick



Washer made of Nylon  
 Outer diameter 8 mm  
 0.5 mm thick

6シリーズ(溝幅8mm)30・60角アルミフレーム用先入れバネナット

数量スライダあり

★★★★☆ 平均満足度 4.3 (この商品のレビューをみる(35件))

ミスミ

通常単価(税別): 49円~  
 (税込単価): 54円~  
 通常出荷日: 在庫1日目 当日出荷可能 17:00まで受付

バネ内蔵により、仮止機能が付いたアルミフレーム用後入れバネナットです。手で軽く押さえると

ナイロン丸ワッシャー(ナイロン)(バック品)

ナイロン丸ワッシャー(ナイロン)(バック品) ★★★★★ (42件の商品レビュー)

【品名】ナイロン丸ワッシャー

# テストビーム実験@ELPH, もちもの

- INTT フルラダー (3台?、理研・奈良女)
- コンバージョンケーブル (short, long, 同軸ケーブル版?)
- バスエクステンダー (最終版、いくつ?)
- ラダー用架台
- 暗幕 (?)
- ROC (2台くらい? どれ?)
  - ROC 用電源 (4~5台、どこから?)
  - 電源用ケーブル (+ 予備、どこから?)
  - ROC - FEM, FEM-IB 通信用光ファイバー (+ 予備、どこから?)
  - BCO distributing ボード
  - ROC - BCO ボード用ケーブル (+ 予備、蜂谷版?)
  - 冷却ファン
- VME クレート (モジュール入れた状態、奈良女)
  - FEM
  - FEM-IB
  - FEM, FEM-IB テストアウトピン用ケーブル (いくつ?、どこから?)
  - FEM, FEM-IB FPGA 書き込み用ケーブル (どこから?)
  - NI ケーブル (どこから?)
- NIM ビン (実験室の状態そのまま、奈良女)
  - NIM モジュール (奈良女)
  - NIM ケーブル (奈良女)
- CAMAC クレート
  - CAMAC モジュール
  - クレートコントローラー用 PC インターフェース
  - USB ケーブル
  - 電源ケーブル
- DAQ PC (Windows10 がよい、理研?)
  - マウス
  - キーボード
  - Web カメラ
  - 電源ケーブル
  - ディスプレイ (地下で使う)
- 実験ノート
- カメラ