

The preliminary results of INTT Testbeam 2021 at ELPH

Cheng-Wei Shih¹ for the sPHENIX INTT collaboration


¹Department of Physics & Center for High Energy & High Field Physics, National Central University, Chungli, Taiwan



The sPHENIX is an upgrade project of the former PHENIX experiment at Relativistic Heavy-Ion Collider (RHIC). The sPHENIX aims to study the quark-gluon plasma by measuring jets, jet correlations and Upsilon's (Υ s) precisely, and cold QCD physics. The tracking system of sPHENIX consists of the MVTX, the TPC and the INtermediate silicon Tracker (INTT). The INTT bridges the tracks of the MVTX and the TPC, aims to improve the momentum resolution for charged particles with the high transverse momentum, and aids the pattern recognition and event synchronization. As a tracker, the detection efficiency of the INTT is required be close to 100% to save all track candidate hits. A testbeam experiment was performed at the end of 2021, at ELPH, Japan. It provides us an opportunity to understand the performance of the INTT more completely. The preliminary testbeam results are presented in this poster.

INTT facts

- 2 layers of barrel silicon strip tracker
- Consists of 56 silicon ladders
- Location : between the MVTX and TPC : The bridge of tracks
- Detection efficiency : $\sim 100\%$: Main goal of this testbeam experiment



Type A sensor : $8 \times 2 = 16$ cells
Type B sensor : $5 \times 2 = 10$ cells




Element	Value	Unit
Strip width	78	μm
Strip length	20 or 16	mm
Material budget	1.08%	X/X_0
# of channel	128	per chip
# of chip	52	per ladder

Ladder energy deposit

- INTT readout : FPHX chip, 3-bit ADC
- DAC Scan was performed to study the full energy deposit distribution with a good resolution


MIP (ch) : 75.42 ± 0.43 ADC



Ladder threshold value : ADC 15 \rightarrow the evidence to expect $> 99\%$ efficiency

Testbeam configuration

- Positron beam with energy of 1 GeV was delivered
- Upgraded testbench DAQ system was employed
- 4 ladders were installed in the testbeam box
 - First ladder was not operated
- External trigger : 2 scintillators coincidence



Tracking algorithm


Strategies :

1. The track trajectory is expected to be a **straight line** due to **low material budget of INTT ladder** and zero magnetic field environment.
2. For each event, the best track is selected and studied.
3. One of 4 **event-profile candidates (111, 110, 101, 011)** are assigned to each event based on track condition.
 - \rightarrow 1 (good): this layer has qualified hit.
 - \rightarrow 0 (bad) : this layer has no qualified hit or no hit.

Categorization


Count the **number of the layers** whose selected chip has at least one hit

- If count = 3 \rightarrow algorithm-1 is applied
- If count = 2 \rightarrow algorithm-2 is applied
- If count = 1 or 0 \rightarrow skip




Algorithm-1

1. Fit all combinations and pick up the one with minimum χ^2 / NDF
2. Check the residual (R^i) of each layer
3. If $<$ tolerance \rightarrow event-profile 111
4. If $>$ tolerance \rightarrow algorithm-2 is applied



Algorithm-2

1. Ignore the layer with **no/outlier hit**
2. Check the position difference of the rest 2 layers, and assign the event profile
3. If $<$ tolerance \rightarrow 110, 101, 011
4. If $>$ tolerance \rightarrow 000




Detection efficiency

- The detection efficiency is based on the counting of the event-profile, defined by the function :

$$\text{Efficiency of layer-0} = \frac{\# \text{ of } 111 \text{ event}}{\# \text{ of } 111 \text{ event} + \# \text{ of } 011 \text{ event}}$$

Run ID	effi. L0 (%)	effi. L1 (%)	effi. L2 (%)
52	$99.65^{+0.11}_{-0.15}$	$99.40^{+0.14}_{-0.18}$	$98.64^{+0.22}_{-0.25}$
53	$99.51^{+0.12}_{-0.15}$	$99.28^{+0.14}_{-0.17}$	$98.24^{+0.22}_{-0.25}$
54	$99.63^{+0.10}_{-0.13}$	$99.49^{+0.12}_{-0.15}$	$98.79^{+0.18}_{-0.21}$
55	$99.57^{+0.11}_{-0.14}$	$99.51^{+0.12}_{-0.15}$	$98.38^{+0.21}_{-0.24}$
57	$99.35^{+0.13}_{-0.17}$	$99.32^{+0.14}_{-0.17}$	$98.29^{+0.22}_{-0.25}$
58	$94.46^{+0.38}_{-0.41}$	$99.47^{+0.12}_{-0.16}$	$98.69^{+0.19}_{-0.22}$
88	$98.71^{+0.28}_{-0.35}$	$99.54^{+0.17}_{-0.24}$	$96.53^{+0.46}_{-0.52}$
89	$99.25^{+0.17}_{-0.21}$	$99.48^{+0.14}_{-0.18}$	$97.11^{+0.32}_{-0.36}$





The efficiency can be up to 99.6 % !

Detection effi. v.s. BCO phase




- TDC module : event process time measurement (BCO phase)



- Another approach : run 58

- # of 011 event : ~ 200
- 011 event may indicates the lack of event process time.



The BCO phase distribution of 011 event seem to be no tendency

Conclusion

- A testbeam experiment with INTT ladders was performed at ELPH.
- The DAC scan was performed, it provides us the evidence to expect $> 99\%$ efficiency.
- The detection efficiency can be up to 99.6%, excellent performance !
- The correlation of the BCO phase and efficiency hasn't been confirmed.