Cylindrical mRwell

μ RWELL Material

ble 3*: μ RWell active area material budget

Name	Material	Thickness (μm)
Windows (x2)	Kapton	25
Drift	Cu (80%)	5
	Kapton (80%)	50
μRWELL Foil	Cu (80%)	5
	Kapton (80%)	50
DLC + prePreg	Kapton	50.2
Readout	Cu-80 (20%)	5
	Cu-350 (80%)	5
	Kapton (20%)	5
	Kapton	50
	Glue	60

^{*}Note: Gas layer is left out of the table

Table 4: μ RWell active area total Cu and **Kapton thicknesses**


Material	Thickness (μm)
Total Kapton	231.2
Total Cu	13

Matt's slide


7/6/22

Cylindrical mRwell

- Implement several layers of material as in previous slide along with cylindrical tile structure in Geant 4
- Comparison of detector structure (smooth cylindrical with Low material budget vs tiles structure with realistic material budget)



- Smooth cylinder
- Ultra thin material
- Has support structure at end based on FIT
 R&D





- Tiled structure along phi (1 m x 1m)
- Materials based on previous slide
- Added some additional layer to mimic cables
- Tile frames are hollow carbon fiber
- Lacks support structure at ends


Cylindrical mRwell


mRwell with ECCE proposal

Updated material and geometry









Cylindrical mRwell and MMG

MMG in Fun4All G4

3 layers 0.018 0.016 0.014 0.012 0.010 0.008 0.006 Material scanning in eta at phi = 1 deg 0.004 0.002

$\times_{0.025}^{-}$ 0.02 0.015 0.01 0.01Material scanning in phi between 0.005 0 to 360 degrees at theta = 0.1 deg

Updated material and geometry mRwell

