


Sep 11, 2022

IMAGING EM BARREL CALORIMETER



EIC Calorimetry Requirements


Barrel CAL in EIC Yellow Report

- Detection of electrons/photons to measure **energy and position**
- Require **moderate energy resolution**
(10 – 12) % $\sqrt{E} \oplus (1 - 3)\%$
 - But! With high electron-pion separation at low momenta.
- Require **electron-pion separation up to 10^4** at low particle momenta
- Discriminate between **π^0 decays and single photons** from DVCS
- **Low energy photon** reconstruction ~ 100 MeV



SCIENCE REQUIREMENTS AND DETECTOR CONCEPTS FOR THE ELECTRON-ION COLLIDER

EIC Yellow Report



DETECTOR GEOMETRY

Imaging Barrel ECal

<https://anl.box.com/s/w5i3e7cmzgznnl1qyjukuhspsn87zwhe>

▪ Hybrid concept

– Imaging calorimetry based on monolithic silicon sensors **AstroPix** (NASA's AMEGO-X mission)
Nuclear Inst. and Methods in Physics Research, A 1019 (2021) 165795


– Scintillating fibers embedded in Pb (Pb/ScFi – Similar to **GlueX Barrel ECal**)
Nuclear Inst. and Methods in Physics Research, A 896 (2018) 24-42

▪ 6 layers of imaging Si sensors interleaved with 5 Pb/ScFi layers and followed by a large chunk of Pb/ScFi section

▪ Total radiation thickness of $20 X_0$

▪ Detector coverage: $-1.5 < \eta < 1.2$ which overlaps with “electron-going” side endcap

Imaging layer – Position info
Pb/ScFi layer – Energy info



ATHENA Detector Proposal Supplemental material

Performance studies



Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

Imaging Layers in Barrel ECAL

Excellent position resolution allowing precise 3D shower imaging

Significantly improved **electron/pion separation** with respect to E/p method

- Impact on DIS cross section and asymmetries


Separation of γ s from π^0 decays at high momenta up to ~ 40 GeV/c.

Precise position reconstruction of γ s (below 1 mm at 5 GeV).

- Impact on DVCS and photon physics

Provides a **space coordinate for DIRC** reconstruction (no need for additional large-radius tracking detector)

- Improving PID for SIDIS and beyond
- Improved tracking resolution for high-momentum particles



Tagging **final state radiative photons** from nuclear/nucleon elastic scattering at low x to **benchmark QED internal corrections**

Imaging layers provide:

- precise measurement of photon coordinates and the angle between electron and photon

Allowing PID of **low energy muons** that curl inside the barrel ECal (< 1.5 GeV with 3T field)

- Impact on J/psi reconstruction, TCS

Imaging Barrel ECal


Imaging layers based on **AstroPix** sensors

- Developed for AmegoX NASA mission; successor of ATLASpix (arxiv:2109.13409).

Simulation conditions:

- Digitization on the level of AstroPix pixel
- 4σ threshold cut applied
- No cracks/non-sensitive regions in the sensor coverage assumed in simulations
- In simulations we explore the possibility of using the AstroPix sensor off-the-shelf
- Layer thickness 0.155 cm + 1 cm of air (cooling):



Layer material	Thickness (cm)
Silicon (sensors)	0.05
Silicon (electronics)	0.015
Copper (cables)	0.01
Kapton (insulation)	0.02
Epoxy (glue)	0.01
Carbon (support structure)	0.05



Pixel size	$500 \mu\text{m} \times 500 \mu\text{m}$
Power usage	$< 1 \text{ mW}/\text{cm}^2$
Energy resolution	10% @ 60 keV (based on the noise floor of 5 keV)
Dynamic range	$\sim 700 \text{ keV}$
Passive material	$< 5\%$ on the active area of Si
Time resolution	25 ns
Si Thickness	$500 \mu\text{m}$
Time tag	$\sim 1 \mu\text{s}$

Barrel ECal - SciFi/Pb geometry

Pb/SciFi layers follow the GlueX Barrel Calorimeter geometry



Simulation conditions


- Digitization in simulations on the level of SiPM grid
- Assumed ~ 2 cm x 2 cm grid size
- Possibility of 2-side readout (spatial resolution). In simulations only one side readout for island clustering (no resolution in z)
- Description of clustering algorithms in backup slide
- Birks constant for ScFi $k_B = 0.126 \text{ mm/MeV}$

2-side readout in final design; GlueX position resolution in z: $1.1 \text{ cm}/\sqrt{E^2}$)

1) Nucl. Instrum. Meth. A, vol. 896, pp. 24–42, 2018, 2) Nucl. Instrum. Meth. A, vol. 596, pp. 327–337, 2008



ENERGY RESOLUTION

The main role of the Pb/ScFi Layers



(GlueX ScFi ECal $\sigma/E = 5.2\%/\sqrt{E} \oplus 3.6\%$)

Used 5 GeV γ s



$$\text{Sampling Fraction} = \frac{\sum E_{\text{active layer}}}{E_{\text{thrown}}}$$



Imaging Layer $\sim 0.6\%$
Pb/ScFi Layer $\sim 10\%$

SPATIAL RESOLUTION

The main role of the Imaging Layers

Cluster level: $\sigma_{\text{spatial}} = (2.32 \pm 0.06)\text{mm}/\sqrt{E} \oplus (1.4 \pm 0.02)\text{mm} @ \eta = 0$

With first layer hit position on top of cluster level: $\sigma_{\text{spatial}} = 0.5\text{mm}$ (i.e. pixel size)




e/ π particle identification




Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

Pion Contamination in Inclusive DIS Physics



pion:electron > $10^3:1$ for $p < 2$ GeV/c in barrel
 No existing calorimetry fully satisfy the requirement



18x275 GeV

10x100 GeV

EIC Yellow Report, arXiv:2103.05419 [physics.ins-det]

Classification Neural Network

- 3 Layers Convolutional Neural Network + 3 Layers Perceptron Network
 - Combined data from AstroPix and Pb/ScFi
 - 3 inserted dropout layers to control overfitting
 - Data formatted to $N_{\text{events}} \times N_{\text{layers}} \times N_{\text{hits}} \times N_{\text{features}}$
 - 4 features (Edep, Rc, eta, phi), energy and spatial information for shower
 - 125k trainable parameters
- Supervised training
 - 100k events (electrons and pions), 80% training, 20% validating
 - 100k electrons and 100k pions benchmarking
 - 20 epochs
 - Statistical uncertainty (binomial dist.) of benchmarking samples is shown


ELECTRON IDENTIFICATION

$e - \pi$ separation

- Separation of electrons from background π in Deep Inelastic Scattering (DIS) processes

- Best e/π separation for $p < 2$ GeV/c
- Comparable to crystal calorimeter at higher momentum
- A factor of 30~100 boost on top of E/p cut for $p > 1$ GeV/c
- 500:1 rejection at lower momentum from when E/p does not work well

Pion-electron rejection efficiency



Standalone
Calorimeter
(no material/no
magnetic field)


Effects from Electron Efficiency

3T Magnetic Field and material budget in ATHENA Geometry

- Simulation with magnetic field and materials
- Two extreme cases added
 - > 95% efficiency
 - > 65% efficiency

The lowest momentum point for electrons at 0.7 GeV is significantly affected by the high magnetic field.


- The rejection factor will go up with lower field.




Update with EPIC Configuration

2 GeV/c particles

ATHENA Configuration



EPIC Configuration




Study for optimizing E/p cut for EPIC configuration is ongoing

- Two dimensional – E/p over thickness

Pion Rejection in EPIC Configuration

- With all materials and magnetic field
- Running simulation to add more points over p
- Similar results achieved with EPIC configuration
 - Smaller radius (80.5 cm)
 - $\sim 1.5\text{T}$ magnetic field
 - Expect improvement with E/p optimization
- More simulations are ongoing to fill momentum spectrum
- Need re-optimization of E/p cuts for the new configuration




Separation of γ and $\pi^0 \rightarrow \gamma\gamma$



Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

Detection of $\pi^0 \rightarrow \gamma\gamma$

EIC Yellow Report, arXiv:2103.05419 [physics.ins-det]





Energy of photons from DVCS versus η from the MILOU simulations for the e+p collisions at beam energies of 18×275 GeV

Figure 11.46: Left: The calculated π^0 momentum spectrum for SiDIS at $e + p 18 \times 275$ GeV collisions, using PYTHIA [1371]. Right: The probability of two photons to merge, calculated [1517] using GEANT4 [1412] for the cell size of 25×25 mm² located at 3 m from the interaction point, for the non-projective geometry. For the projective geometry the results for $\eta > 3.5$ would be close to the non-projective curve at for $\eta = 3.5$.

Hard Limit for Cluster Merging

- For **modular calorimeters**, **cell size** is the limit
 - No reliable splitting for hits in neighboring cells or the same cell
- For **pixel sensors**, the shower profile is used at different depths



Shower profile from img layers for 5 GeV γ s



I. Larin, HyCal Clustering

Detection of $\pi^0 \rightarrow \gamma\gamma$

15 GeV π^0 example



Merging probability for $\pi^0 \rightarrow \gamma\gamma$

π^0 decays in barrel region

Detection of photons at **R = 0.8 m**


Cut out-of-acceptance events

Cut very low energy events
(photons with energy > 100 MeV used)

Hard limit of merging

- Cell size for modular calo
- For AstroPix: 6 FWHM of shower profile at the layer where at least 90% of gammas fired a hit

Used shower profile (6FWHM)



Quick check at different geometry: shower profile from ATHENA simulation w/ 3T field but at r = 80 cm.

Cluster splitting π^0 invariant mass reconstruction




Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

Motivation


Goal: Reconstruction of π^0 Invariant Mass at low energies

- **Test ground for Question:** how well can we **split energetically gamma clusters** when showers are close to each other in SciFi layer
 - Current SciFi granularity in the simulation ~ 1.1 deg
 - Close showers (such as multi-occupancy in one or a couple ϕ grids) can be treated as one cluster in SciFi section
- Noted that clustering algorithm applied in imaging and SciFi separately.
- Currently in clustering algorithm cluster splitting switched off. Here following study shows extreme case by limited algorithm of clustering.
 - 2 type of reconstruction cases (with accurate measure of the particle entry point by imaging layer)
 - 2 clusters in imaging layers and 2 clusters in SciFi
 - 2 clusters in imaging layers and 1 cluster in SciFi
- Evaluate energy splitting based on imaging layer energy **when we have one cluster in SciFi and 2 clusters in imaging layer**



Gammas separation in SciFi

Neutral Pion Study at Generated Level (SIDIS sample)



ϕ granularity
(assuming 2 cm readout)
 $\Delta\phi @ 103 \text{ cm} \sim 1.1^\circ \sim 0.020 \text{ rad}$
 $\Delta\phi @ 80 \text{ cm} \sim 1.4^\circ \sim 0.025 \text{ rad}$

- How many events falling into grid
 - In 1 ϕ grid:
 - 2% @ 103 cm
 - (3% @ 80 cm)
 - In 2 ϕ grid:
 - 4% @ 103 cm
 - (5% @ 80cm)

Procedure

Reconstruction of π^0 invariant mass at low energies

- **Calibration factor applied** to account for slight energy dependence of sampling fraction
- Position information from Imaging layer and energy information from SciFi layer to reconstruct invariant mass
- Double-occupancy in 1 readout module in SIDIS π^0 sample is below 3%

In a case of 2 clusters in Imaging layer matched 1 cluster in SciFi:

- Isolate the energy of the two clusters to reconstruct π^0 using **energy splitting based on Imaging layer** energy and the effect on sigma of invariant mass distribution is quite small

Used 2 GeV Single π^0 Simulation


ENERGY AND INVARIANT MASS $M^2 = 2E_1E_2(1 - \cos \theta_{\gamma\gamma})$

2-matching clusters in Imaging and 2-matching clusters in Pb/ScFi

*Matching based on MC truth information

$E_{\text{cluster threshold}} = 0.2 \text{ GeV}$

- Identify two γ s from a neutral pion
 - Position info from imaging layer
 - Energy info from Pb/ScFi layer
- Calibration factor applied to account for slight energy dependence of sampling fraction
- Invariant mass calculated from gammas energy and opening angle




Used 2 GeV Single π^0 Simulation


CLUSTER ENERGY AND ENERGY RATIO

2-matching clusters in Imaging and 1-matching cluster in Pb/ScFi

1-matching Pb/ScFi Cluster Energy



Energy splitting factor




Used 2 GeV Single π^0 Simulation


INVARIANT MASS $M^2 = 2E_1E_2(1 - \cos \theta_{\gamma\gamma})$

Position info from Imaging and Energy info from Pb/ScFi

2-2 matching invariant mass



2-1 or 2-2 matching Invariant mass



Backup



Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

Particle PID





Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

MUONS IN BARREL

for 3T field

- Muon/pion separation in **central region** determined from information from the **Barrel ECal** and **HCal**
- Results for single particle simulation, **see details in the following slides**



- **At $\eta = 0$: muons $> \sim 1.5$ GeV/c reach HCal, and $< \sim 1.5$ GeV/c curl inside the BCal** (different approach to analysis)
 - This discontinuity (in reaching HCal) is rapidity dependent
- **Neural Network** studies in ECal done for $\eta = (-1, 1)$, **ECal+HCal studies** and **E/p studies in ECal** done for $\eta = 0$
- Further improvements to muon/pion separation from PID detectors expected (DIRC)

SUMMARY AND OUTLOOK

1. **Hybrid Imaging ECAL calorimeter** proposed for the future Electron-Ion Collider
 - Scintillating fibers embedded in Pb and imaging calorimetry based on silicon sensors (AstroPix)
2. Novel technology, yet with limited risk
3. This, cost-effective for its excellent performance, design fulfills and further improves the Yellow Report requirements and opens new physics opportunities:
 - **Excellent** Energy and Spatial resolution
 - **Electron-pion separation** at low particle-momenta
 - Separation of two gammas from **neutral pion up to 45 GeV**
 - Muon PID, radiative processes, ...
 - Can serve as DIRC tracking layer and inner HCAL

Cluster splitting π^0 invariant mass reconstruction



Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

Used 5 GeV Single π^0 Simulation

$\pi^0 \rightarrow \gamma\gamma$ INVARIANT MASS



$$M^2 = 2E_1E_2(1 - \cos \theta_{\gamma\gamma})$$

2-matching clusters in Imaging and 1-matching cluster in Pb/ScFi

$$M^2 = 2E_1E_2(1 - \cos \theta_{\gamma\gamma})$$

with Energy-based splitting using Imaging layer

$$M^2 = 2 \frac{E}{2} \frac{E}{2} (1 - \cos \theta_{\gamma\gamma})$$




Used 2 GeV Single π^0 Simulation

ENERGY AND INVARIANT MASS $M^2 = 2E_1E_2(1 - \cos \theta_{\gamma\gamma})$

2-matching clusters in Imaging and 1-matching cluster in Pb/ScFi


Energy resolution of each decayed γ

with Energy-based splitting using Imaging layer



$0.5 < E_\gamma < 1 \text{ GeV}$


$1.5 < E_\gamma < 2 \text{ GeV}$



Long tail

Invariant mass

with Energy-based splitting using Imaging layer



Nominal mass of π^0 :
134.97 MeV

Procedure


Reconstruction of π^0 invariant mass at low energies

- Calibration factor applied to account for slight energy dependence of sampling fraction
- Position information from Imaging layer and energy information from SciFi layer to reconstruct invariant mass
- Double-occupancy in 1 readout module in SIDIS π^0 sample is below 3%

In a case of 2 clusters in Imaging layer matched 1 cluster in SciFi:

- Isolate the energy of the two clusters to reconstruct π^0 using energy splitting based on Imaging layer energy and the effect on sigma of invariant mass distribution is quite small


ATHENA Barrel ECal



- **Geometry**

- 12 staves, 6 AstroPix layers
- $R_{\min} = 1.03$ m, Length = 4.05 m, Thickness ~ 40 cm
- AstroPix: 1.155 cm per layer (1 cm of air), $1.8\% X_0$
- Pb/ScFi: 1.586 cm per layer, $\sim 1.08X_0$

- Contains negative Endcap inside (partially serves as the Endcap detector)



ASTROPIX SENSOR LAYERS

For **6 layers** of imaging layers that cover $-1.5 < |\eta| < 1.2$ the AstroPix sensors area is about **174 m²**.

Large Si detector arrays in advanced stage (large scale prototypes)

- ATLAS Inner Tracker - silicon strips¹ (ITk pixel) 160 m² (50 million channels)
- CMS high granularity calorimeter² ~ 600 m² (6.5 million channels)
- AstroPix sensors (derived from ATLASpix) will be used in the **AMEGO-X NASA mission**, which is a 40 m² experiment sent into space. We expect AstroPix-v3 to be the final version and submitted in spring 2022, and ready in fall 2022.
- We plan to use it off-the-shelf, **meaning with no design modifications**.

Advantages of AstroPix with respect to pixels used in e.g. ATLAS

- AstroPix has very low power consumption (used in space) - 1000 times smaller power consumption per cm² than ITk pixel
- AstroPix is a monolithic sensor - less complicated structure
- No bump bonding - less risk of damaging sensors

¹ arXiv:2105.10367, ATLAS ITk Pixel Detector Overview

² arXiv:1802.05987, The CMS High-Granularity Calorimeter for Operation at the High-Luminosity LHC2

GlueX Energy Resolution

The resolution $5.2\%/\sqrt{E} \oplus 3.6\%$ is for the typical momentum range for π^0 and η in GlueX and integrated over typical angular distributions for π^0 and η production (0.5-2.5 GeV).




Figure 32: a) Measured and simulated η width as a function of energy for symmetric decays, where both photons are required to be within 0.1 GeV of each other. b) The energy resolution of single photons calculated under the assumption that only the energy resolution contributes to the η width. The curves are fits based on Eq. 4 (Color online)

We note that the response of the calorimeter averaged over its length, as done for the η sample in Fig. 32, is not described well with Eq. 4 and **has a large correlation between the two parameters (-0.89)**. Nevertheless, in order to characterize the performance of the BCAL between 0.5 and 2.5 GeV, we take the fitted energy-resolution parameters integrated over the angular distributions for π^0 and η production to obtain a typical energy resolution for our detector of $5.2\%/\sqrt{E} \oplus 3.6\%$. In order to estimate the resolution at high energy, we use the MC that describes our data at low energy (Fig. 33) and results in a constant term of **less than 1.7%**. However, to verify this expectation, we would need additional data reaching to higher energy.

GlueX Energy resolution




Figure 33: Simulated fractional energy resolution for data at different angles from the target for the distribution in Fig. 31a. At shallow angles the stochastic term increases and the energy leakage generates a non-zero constant term. The MC data points are fitted to Eq. 4 with the results shown in the legend. (Color online)

e/ π particle identification




Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

Performance Impact

- Electron/Pion Separation

 - Imaging layers significantly improve electron/pion separation





With ScFi only: pion suppression based on E/p cut utilizing sum of deposited energy at different calorimeter depth

With imaging layers: order of magnitude improvement in pion suppression with ML methods utilizing 3D spatial and energy information of the shower profile

Yellow Report requirement: R_π up to 10⁴

Performance Impact

- Full geometry of ATHENA
 - Materials from other PID detectors inside barrel
 - Efficiency for electron drops to ~91%




Pion Rejection Power

Solid line: 6 AstroPix Layers

Dashed line: 9 AstroPix Layers

- Best e/pi separation for $p < 2$ GeV/c
- Comparable to crystal calorimeter at higher momentum
- A factor of 30~100 boost on top of E/p cut for $p > 1$ GeV/c
- 500:1 rejection at lower momentum from when E/p does not work well




Number of imaging layers

3D shower imaging:


- **3 layers** at the beginning of the shower development to capture the **signals of the shower/preshower starting point** for most of the electrons and photons.
 - Photons may shower at greater depth, the study of photon shower hits distribution shows this
 - Important for photon physics for the position resolution and π/γ separation based on shower profile
- **2 layers** needed to **sample the most dense part** of the shower development
 - Important for e/π shower shape separation, particle PID
 - Important for full 3D cluster reconstruction. Full 3D cluster reconstruction is affected by small number of hits (visible for low energy particles).
 - 3D cluster reconstruction important for spatial resolution for photons.
- **1 layer** needed **for the shower tail**
 - Important for e/π shower shape separation, particle PID (hadrons, muons)

First img layer that photons leave a hit at


First img layer with registered hit for 0.5 GeV




First img layer with registered hit for 1 GeV




First img layer with registered hit for 2 GeV




First img layer with registered hit for 5 GeV









First img layer with registered hit for 10 GeV



First img layer with registered hit for 20 GeV




Average number of hits per layer




Average number of hits in 6 layers

Number of hits



Deposited energy (reconstructed)




Example of cluster reco optimization

Work in progress
S. Kaur


Nhits = 18 , min edep = 0.5MeV , distXY = 2.5mm

Nhits = 6 , min edep = 0.5MeV , distXY = 2.5mm



Initial optimization for high E
photons > ~1 GeV

Photons



Initial optimization for low E
photons < ~1 GeV
~ 50%


Pion Rejection Power - Different Nb of Layers

9 layers → 6 layers
about a factor of 1.5 in pion rejection power

9 layers → 7 layers
similar performance at higher momentum



6 layers → 7 layers
small improvement at lower momentum as compared to

Standalone performance, no material in front,
no field



Pion Rejection Power - Different Nb of Layers

- With 5 layers, we will experience a drop of about 20~50% for the rejection power
- Low energy point affected by magnetic field
- Efficiencies as shown below for 6 lmg layers



Reconstruction methods



Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

Clustering

Current in juggler analysis framework, the clustering is done by

1. digitization -> simulation hits to readout signals
2. readout reconstruction -> readout signals to energy/timing/position/etc (calibration)
3. proto-clustering -> group hits following certain algorithms
4. cluster reconstruction -> reconstruct position/energy/etc from group of hits

Two clustering algorithms are available now

1. Island clustering for 2D hits
2. Topo clustering for 3D hits

Island Clustering

Group all neighbouring hits


Parameterized conditions for finding neighbors

Distance in local-XY, local-XZ, local-YZ,

local-XY scaled by cell dimensions,

global eta-phi, global R-phi

Parameterised minimal energy to be qualified as cluster center, and minimal energy to participate clustering




Island Clustering Splitting

Cluster splitting is available for Island Clustering

Split based on Local maxima that are qualified as cluster center

Hits energy split based on local maxima's energies and distances



Topo Clustering

Similar to Island clustering but works for hits from several layers, currently used for imaging layers

Hits at the same layer, local-XY

Hits from different layers, layer id difference and global eta-phi


Hits from different sectors, global distance

No splitting implemented currently


Mostly MIP signals in imaging pixels

3D Clustering Samples

All Hits




Clusters and True gamma positions




3D Clustering Samples

All Hits



Clusters and True gamma positions




Readout



Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

Dynamic Range



- Dynamic range for AstroPix v1: 700 KeV
- To be extended to a few MeV for the proposed calorimeter
- 3 MeV range will cover over 99% of the deposited energy (2 GeV electron simulation)

Occupancy

- Readout system: **two-levels aggregators**
- Each stave of the detector: **8 first-level aggregators** (~0.3 m²)
 - collect the signals from the covered area and send the data to the second-level aggregators
- **2nd lever aggregator**: inject the AstroPix layers data into the main data stream; also participate in the trigger forming for the whole ATHENA detector.

Layer Number	Stave Area (m ²)	N _{pix} / Stave	N _{pix} / Aggregator
1	2.24	89k	11k
2	2.30	92k	11k
3	2.36	94k	12k
4	2.42	97k	12k
5	2.48	99k	12k
6	2.54	101k	13k
7	2.60	104k	13k
8	2.66	106k	13k
9	2.72	109k	14k

Occupancy






Figure 18: The maximum number of hits in first-level aggregators from single-particle simulation with 20 GeV electrons. The electrons were uniformly generated to scan the whole geometrical acceptance of the barrel calorimeter. One stave of the barrel calorimeter, including 9 AstroPix layers and 8 aggregators per layer, is shown here. Each block in the plot represents an aggregator. The hot regions at both ends are due to geometrical effects caused by endcap calorimeters.

Ionization radiation and neutron flux



- Maximum ionizing radiation dose from e+p collisions at the highest EIC luminosity ($10^{34} \text{ cm}^{-2} \text{ s}^{-1}$): ~ 1 Rad/year
- Neutron flux: 10^8 neutrons/cm² per year at the top luminosity (two order of magnitude lower than the near-beam-line detectors)


Reconstruction of π^0




Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

2 GeV photons, y position


Hit position in Layer 1




Hit position in Layer 2




Hit position in Layer 3




Hit position in Layer 4



Hit position in Layer 5




Hit position in Layer 6




2 GeV photons, z position


Hit position in Layer 1




Hit position in Layer 2




Hit position in Layer 3




Hit position in Layer 4



Hit position in Layer 5




Hit position in Layer 6




FWHM of shower for layer 1, 2, and 3

Hit y-distribution width




Hit z-distribution width




For low energy (0.5, 1, 2 GeV) in 1st layer we see double-peak in y distribution (e+e- from interaction before calorimeter). FWHM reflects the width of the whole hit position distribution here, not individual peaks.

FWHM of shower for layer 1, 2, and 3

Hit y-distribution width




Hit z-distribution width




For low energy (0.5, 1, 2 GeV) in 1st layer we see double-peak in y distribution (e+e- from interaction before calorimeter)

First img layer that photons leave a hit at


First img layer with registered hit for 0.5 GeV




First img layer with registered hit for 1 GeV




First img layer with registered hit for 2 GeV




First img layer with registered hit for 5 GeV



First img layer with registered hit for 10 GeV




First img layer with registered hit for 20 GeV



Physics Impact

● Photon physics

$\gamma\gamma$ Merging Probability of π^0 decay at R = 1.03 m



Yellow Report: Separation required up to 20 GeV

Separation between π^0/γ

With imaging layers: using 3D shower profile separation of γ s from π^0 decays at high momenta **up to ~40 GeV/c** at R = 1.03 m and normal incident angle.

With ScFi only:

- Effective cell size of 2 cm × 400 cm
- Separation **driven by timing resolution**. Timing resolution at GlueX results in z-position resolution of the order of 3.1-2.2 cm for neutral showers at 0.5-5 GeV¹
- In the ideal case for balanced γ s energy and requiring about 2σ separation (6 cm) between showers - separation **up to ~7 GeV (blue curve)**

Spatial resolution of γ

- From imaging layers: of the **order of ~1 mm** (1 GeV γ)
- For GlueX ScFi: of the order of **centimeters** from timing resolution (~150 ps for 1 GeV γ)


¹ See Figure 28 in Nucl. Instrum. Meth. A 896 (2018) 24-42, Construction and Performance of the Barrel Electromagnetic Calorimeter for the GlueX Experiment

NEUTRAL PIONS $\pi^0 \rightarrow \gamma\gamma$

Invariant Mass

- Identify two γ s from a neutral pion
 - Position info from imaging layer
 - Energy info from Pb/ScFi layer
- Calibration factor applied to account for slight energy dependence of sampling fraction
- Invariant mass calculated from gammas energy and opening angle

Reconstructed Invariant Mass




NEUTRAL PIONS $\pi^0 \rightarrow \gamma\gamma$


Energy and Position Resolution at Cluster Level

- Reconstruction of π^0 from two γ s
- Possible to have even better improvement with first layer hit information


Energy



Pseudorapidity



Azimuthal angle



AstroPix





Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

AMEGO-X at NASA

All-sky Medium Energy Gamma-ray Observatory eXplorer



- ❖ AMEGO-X operates both as a Compton and pair-production telescope to achieve unprecedented sensitivity between 100 keV and 1 GeV
- ❖ Gamma-ray Detector (GRD)
 - ❖ Tracker Module (AstroPix), Calorimeter
- ❖ Anti-Coincidence Detector (ACD)
 - ❖ To reject charge particles (background)





AstroPix for AMEGO-X

AstroPix Sensor

- ❖ AstroPix are CMOS sensors based on ATLASPix3 sensors (arxiv:2109.13409)
- ❖ AstroPix v1 ($4.5 \times 4.5 \text{ mm}^2$ chip)
 - ❖ 18×18 pixel matrix with $200 \mu\text{m}$ pitch
- ❖ Timing resolution $\sim 25 \text{ ns}$
- ❖ Low power dissipation
- ❖ Targeted energy resolution is $< 10\%$ at 60 keV
- ❖ AstroPix v2 is under testing ($10 \times 10 \text{ mm}^2$ chip)
 - ❖ 35×35 Pixel matrix with $250 \mu\text{m}$ Pixels




ATLAS-Pix3 Energy Resolution




AstroPix for AMEGO-X

AstroPix Setup

- ❖ **GE**neric **C**onfiguration and **C**ontrol System (GECCO)
- ❖ Connection to FPGA - NexysVideo (Xilinx Artrix-7)
- ❖ Vivado Design Suite HLx to program ASIC chip
- ❖ Assembly and testing of AstroPix sensors with GECCO boards through FPGA







AstroPix-v2 carrier board




AstroPix for AMEGO-X (V1)

Testing of CMOS sensors

- ❖ Data is collected with different γ & β - radiation sources
- ❖ Data is analyzed for pulse amplitude distribution and rise time
- ❖ AstroPix setup will be integrated with ATLAS telescope planes using HSIO system



$$\text{Energy resolution} = 2.355 * \text{Sigma/mean}$$



ZONE	REVISION HISTORY	DATE	APPROVAL
	DESCRIPTION		

- NOTES:
- SEE BICAL ASSY. PROCEDURE D00000-01-07-P000.
 - ITEM B TO BE ATTACHED TO THE NON-RING SIDE OF WEDGE PLATES. FULL COVERAGE OF WEDGE FACE.
 - SUGGESTED SOURCE OR JLAB APPROVED ALTERNATIVE:
 - MONMASTER CARR SUPPLY COMPANY
 - (609) 488-1000
 - HTTP://WWW.MONMASTER.COM
 - ESTIMATED WEIGHT 57600 LBS.

QTY	DESCRIPTION	UNIT	REMARKS
66	MONMASTER-CARR FLAT WEDGER .25	1100P AL	
66	15	SOC 40 CAP SCREW 75-20 UNF X .75 LG	STAINLESS STEEL TYPE 316
2	14	000000-01-07-2006	PAWL
66	13	000000-01-07-2007	SPACER
8	12	HEX NUT 20-20 UNC	SILICON BRONZE
8	11	SOC 40 CAP SCREW 75-20 UNF X 2.00 LG	STAINLESS STEEL TYPE 316
32	10	MONMASTER-CARR FLAT WEDGER .25	FIBERGLASS
8	9	000000-01-07-2008	SLEEVE
66	8	MONMASTER-CARR 3648A9	RAPID TAP W/BLIND G DRIVE W/ WIDE X .0025 THICK
12307	7	MONMASTER-CARR 8616A12	O-RING COMP STKX 3/32 DIA.
752	6	MONMASTER-CARR 8807A200	FLAT WEDGER .30
276	5	HEX NUT 20-16 UNC	STAINLESS STEEL TYPE 316
276	4	SOC 40 CAP SCREW 28-16 X 2.00 LG	SILICON BRONZE
1	3	000000-01-07-1902	WEDGE SUB-ASSEMBLY 3
1	2	000000-01-07-1902	WEDGE SUB-ASSEMBLY 2
46	1	000000-01-07-1901	WEDGE SUB-ASSEMBLY 1

DETECTION Lab

DETECTION BARREL CALORIMETER CALORIMETER SUB-ASSEMBLY

D00000-01-07-1000

DATE: 10/1/2010

BY: [Signature]

APP'D: [Signature]

SCALE: 1/2

Muon PID




Argonne National Laboratory is a
U.S. Department of Energy laboratory
managed by UChicago Argonne, LLC.

Muons in barrel region


- For energies **below $\sim 1.5 \text{ GeV/c}$** muons curl inside the Barrel ECal

Energy reconstructed in BECAL/Momentum




Muons reach only a few first layers of BEcal; deposit partial energy inside the BEcal and **curl back**

Energy reconstructed in BECAL/Momentum



Muons curl completely inside the BEcal and leave whole energy inside

Energy reconstructed in BECAL/Momentum



- Muons** curl completely inside the BEcal and leave whole energy inside
- Muons** punch through BEcal, and curl back to stop in BEcal
- Muons** punch through BEcal, and don't curl back (MIPs signal)

Sampling fraction of Barrel ECal = ~ 0.1


Muons in barrel region

Example of **muons** and **pions** at $p = 0.5 \text{ GeV}/c$ at $\eta = (-1,1)$


Efficiency: 98.9% \rightarrow Rejection Power: 6.6

Efficiency: 95% \rightarrow Rejection Power: 9.7

Total Energy deposit in ScFi/Pb



NN output likelihood



Muons in barrel region

- For energies **below ~ 1.5 GeV/c** muons **curl inside the Barrel ECal**
- **Barrel ECal with 3T field “serves as” an HCal**

PID Cuts

- 1) **Method 1:** Using only information from ScFi in Barrel ECal (Energy losses in layers)
 - a) Cut on E/p from single ScFi/Pb Calo Layer or sum of all ScFi/Pb Calo Layers
- 2) **Method 2 (showing impact of imaging layers):** ML supported, using information from **ScFi/Pb and Imaging layers**
 - a) Input which encodes the energy and spatial distribution of the particle's shower
 - **Four features** for each hit: η , ϕ , E, $R = \sqrt{x^2 + y^2}$; (no η for ScFi/Pb)
 - Values normalized to [0,1]
 - Three-layers convolutional neural network and three-layers perceptron network
 - Network outputs: **likelihoods** of the input particle to be **identified as a muon or a pion**.
Likelihood cut: **95% of muon efficiency**


Muons in barrel region

Example of **muons** and **pions** at $p = 0.5 \text{ GeV}/c$ at $\eta = (-1,1)$

Efficiency: 98.9% \rightarrow Rejection Power: 6.6

Efficiency: 95% \rightarrow Rejection Power: 9.7

Total Energy deposit in ScFi/Pb



NN output likelihood

