



Contribution ID: 24

Type: **Contribution Talk**

## A 3ps Cryogenic Time-to-Digital Converter for Time-Correlated Single Photon Counting

*Thursday, December 1, 2022 8:30 AM (20 minutes)*

We present a time-to-digital converter (TDC) that simultaneously achieves very low power and picosecond timing resolution when operated in a cryogenic (4K) environment. Such a TDC is an enabling technology for quantum secure direct communications which require high bandwidth time-correlated single photon counting. The proposed TDC uses a two-step architecture in which the input time delay is first coarsely digitized through a ring-oscillator based counter, and the residue is then finely digitized by a Vernier delay line “fine TDC.” The TDC is implemented in an FD-SOI process, and back-gate tuning is used both to correct threshold variation due to cryogenic operation and to enable tuning of the fine TDC delay elements with very little overhead. Simulations show a fine TDC resolution of 2.7 ps with a dynamic range of  $> 50$  ns at  $\frac{1}{2}$  LSB rms jitter, with power consumption of  $< 500$   $\mu$ W per channel. A prototype chip has been fabricated and is currently undergoing test.

**Primary authors:** QUINN, Adam (Fermilab); BRAGA, Davide (Fermilab)

**Presenter:** QUINN, Adam (Fermilab)

**Session Classification:** WG1: Solid State Detectors and ASICs

**Track Classification:** WG1: Solid State Detectors and ASICs