

INTT Ideal Geometry

Joseph Bertaux
Rachid Noucier


Outline

- Measure and catalog the positions of key points
 - Total of 20 positions to be noted:
 - 2 holes at the north and south ends of the ladder
 - (4 positions)
 - 4 marks at the corners of each of the 4 sensors
 - (16 positions)
- Measurements were taken by survey group using the OGP machine

Motivation

- This data will be useful in the tracking reconstruction
 - Each track allows fitting parameters for the offset of ladder, sensor, or pixel positions from nominal
 - These extra fitting parameters are
 - dx, dy, dz (global cartesian shift)
 - α, β, γ (Tait-Bryan ZYX Euler angle rotation)
 - There are sets of these parameters for each “index”
 - During reconstruction, parts of the detector can be assigned an index
 - Parts with a common index share a transformation
 - e.g., each sensor has its own index, and its pixels share a transform

OGP Process



Nominal Ladder Marks





Image credit:
Dan Cacace
dcacace@bnl.gov

Nominal Ladder Positions



OGP File Example

Machine Serial Number: SVL6252331

Page: 1

```
=====
Routine Name                               Run #      Date & Time
=====
INTT-Ladder-Survey-East.RTN                10 Tue Oct 12 10:01:47 2021
=====
```

```
=====
Feature      Unit  Nominal  Actual  Tolerances  Deviation  Exceeded
=====
```

Step 10 - Sensor A - Cross 1

X Location	mm	+013.56485	+013.48306		-000.08179	
Y Location	mm	+005.99526	+005.98173		-000.01353	
Z Location	mm	+000.15466	+000.11972		-000.03494	

Step 12 - Sensor A - Cross 2

X Location	mm	+115.06485	+115.00606		-000.05879	
Y Location	mm	+005.99526	+005.97168		-000.02358	
Z Location	mm	+000.15466	+000.27978		+000.12512	

Step 14 - Sensor A - Cross 3

X Location	mm	+115.06485	+115.01265		-000.05220	
Y Location	mm	+027.99526	+027.96840		-000.02686	


Procedure

- The OGP machine data has already been taken
- Data was stored in .txt files
- Wrote a macro to extract the data from from these files and store it in a root TTree
 - Branches for measured x,y,z coordinates (mm)
 - Branches for nominal nx, ny, nz coordinates (mm)
 - Branches for deviations dx, dy, dz (mm)

Procedure

- Created an additional branch to store a unique reference string
 - e.g., “B1L010_snsr_A_crss_1”
 - e.g., “B0L103_ndcp_2”
 - “..._snsr_%s_crss_%i” are for the 4 marks (labeled 1, 2, 3, 4) on each sensor (labeled A, B, C, D)
 - “..._ndcp_%i” are for the 4 holes (labeled 1, 2, 3, 4) on the ladder
- Difficult to work with strings directly in a root session
- Can use in macros just fine
 - Wrote a custom DrawComponent function to visualize components
 - Uses std::find(...) to determine if an entry is for a specific subcomponent
 - e.g., DrawComponent(“B1L010”, ...) draws all the points for that ladder:

ROOT Position Reproduction



To Do:

- Now that the position data has been transferred to a .root file, it will be easier to work with
- This might already contain the local dx, dy, dz deviations we are looking for
 - (The “Deviation” column in the OGP file)
 - However, it does not contain these values for the holes
 - Only for the marks 1-4 for each sensor
- Now need to transform these to the global frame based on which ladder it was in
- Need to compute alpha, beta, gamma (Tait-Bryan Euler angles) for each sensor