

ECT Status Update: Production and Test of the ETA Redesign for the Enevlope Changes

Stefano Gramigna (sgramigna@roma2.infn.it) on behalf of the ePIC ECT working group:

C. Ammendola, R. Ammendola, M. Bondì, A. D'Angelo,
R. Di Salvo, A. Fantini, L. Lanza, S. J. Lee, G. Nobili, E. Sidoretti


In collaboration with:

G. Bencivenni, G. Felici, M. Gatta, M. Giovannetti, G. Morello,
M. Poli Lener, G. Sekhniaidze, L. Torlai, G. Zunica

Jan 16th 2026 – MPGD DSC ECT meeting





Outline





- Production of the engineering test article (ETA)
- Preparation of the test beam
- Preliminary results of the TB data analysis
- Redesign: study of the acceptance

ETA Production



ETA Main Components and Assembly





Gluing Tests and Glue Transfer Technique



Quality Control of the GEM Foils



- Optical inspection
- Capacitance measurement
- Resistance measurement
- Insulation test up to ~~500V~~
~~(Requires N2 enclosure)~~







Performed on arrival and after the gluing, before shipping the foils back to CERN

One sector already shorted on arrival, **no new sectors were damaged in the operations**

The gluing procedure is “clean”

GEM Gluing



Araldite AY103 epoxy deposited in a 3 mm wide strip



GOOD for mechanical stability, no overflow, no holes occluded

BAD for gas tightness, internal sealing with Araldite 2011 required

4 GEMs Glued in total (2x ETA Quadrants, 2x CS prototypes)

The technique is serviceable, there is room for improvement

ETA Assembly and First Conditioning






μ -RWELL + R/O PCB Manufactured at CERN MPT Workshop

Final assembly and first detector conditioning also performed at CERN

Nr. 2 ECT ETAs ready for the second week of the test beam (1 w/ grids and 1 w/o)

Test Beam Preparation


Setup and Detector Arrangement




DET	Pitch (μm)	Active Area	Readout	Capacitive Sharing
TRK	400	$10 \times 10 \text{ cm}^2$	2D XY	No
QUAD	600	$R = 45 \text{ cm}$	2D XY	No
CS	1200	$46 \times 40 \text{ cm}^2$	2D XY	3 Layers (300 μm)
TRG	NA	$15 \times 15 \text{ cm}^2$	SiPM	NA

All MPGDs operating with Ar:CO₂:CF₄ (45:15:40)

DAQ




Trigger Signal
Injection Board




HIROSE to Panasonic
Transition Board


Data Pipeline




Trigger



×9 Ø1 mm wavelength shifter fibers
Bundled and embedded in the groove






Onsemi J-Series 30020
3x3 mm² SiPM Area




Non-amplified signal output
from cosmic rays

Also provides a time reference (t_0) to selected APVs for μ TPC reconstruction

HV Slow Control and Current Monitor



Trackers powered in parallel



1 HV Channel per type of electrode

Same electrodes of different detectors grouped together

4 HV channels in total

DUT's electrodes powered individually

1 HV Channel per electrode per detector

16 HV channels in total


Finer diagnostics and HV regulation

Preliminary Results


Position and Efficiency Maps




Highest charge cluster position QUAD1 (w/ grids)



Highest charge cluster position QUAD2 (w/o grids)



Residuals Distributions



$$\sigma_{x \text{ eff}} = 80 \mu\text{m}$$

Lower view
520 μm strips width

$$\sigma_{y \text{ eff}} = 141 \mu\text{m}$$

Upper view
90 μm strip width

$$\sigma_{x \text{ eff}} = 120 \mu\text{m}$$


Upper view
90 μm strip width

$$\sigma_{y \text{ eff}} = 88 \mu\text{m}$$


Lower view
520 μm strip width

The two quadrants are rotated by 90 degrees with respect to each other, hence the X-Y exchange


Size and Charge of the Signal Clusters



Cluster Size VS GEM Voltage *



Cluster Charge VS GEM Voltage *






- QUAD1
- QUAD2

**Charge sharing
visibly skewed
in favor of the wider
strips of the lower
view**

* WELL = 550 V
TRSF = 4.5 kV/cm
DRFT = 2.5 kV/cm

First Resolution and Efficiency Estimates



Preliminary performance satisfy requirements @ HV GEM = 350V

Generous leeway for safe detector operation and optimization



* WELL = 550 V
TRSF = 4.5 kV/cm
DRFT = 2.5 kV/cm

Conclusions


- Two **size 1 ETAs** for the ECT **produced and tested successfully**
- **GEM stretching** technique **well consolidated**
- **Gluing** procedure serviceable but **could be improved**
- **Many new ancillary systems** were **deployed** for the test beam
- The **preliminary results** from the analysis are encouraging:
 - **Spacer grids** do **not** seem **necessary** at the tested dimensions
 - **Charge sharing** between the two views is **not even**, needs optimizing
 - **First estimates for resolution and efficiency** fully **within requirements**
 - **Large operability range** available for further optimization

ECT Redesign: Acceptance Study

Purpose of the Study



LEPTON SIDE



HADRON SIDE


Before the envelope change, active area coverage near the beam pipe was maximized using **3 different module layouts**

Changes to the disks' location along the beam direction **might render this optimization** of the modules' geometry **unnecessary**


Project recommended a reassessment, taking **SVT coverage** along η into account

Falling back to **2 or even 1 module layouts** could greatly **simplify design and serial production**

Sources and References



The design of the SVT maximizes angular coverage **for each individual layer**, arranging sensors as close as possible to the edges of the envelope (5 mm from beam pipe)




Many thanks to Ben and Ernst
for their helpful explanations on the matter

Envelope drawings released on **09/22/2025**
were adopted as reference for all coming
geometric considerations

Simplification of the Problem: SVT Layers




The **sensitive surface** of each SVT layer is assumed **as large as the surface of the relevant envelope volumes facing the IP**



Only the first SVT barrel layer was included in the study


SVT barrel layers affect a region of **little to no interest** for the optimization of the **ECT modules' central cavity**

Simplification of the Problem: ECT Layers



ECT sensitive surfaces account for **manufacturing constraints**:



- **Z**: Sensitive surfaces are offset 10 mm from the envelope outer surfaces (9 mm detector stack + 1 mm mechanical interfaces)
- **R_{in}**: Inner radius is offset by 20 mm (15 mm support frame + 5 mm assembly clearance)
- **R_{out}**: Outer radius is offset by 50 mm to leave space for FEBs and services



DISCLAIMER: This study is not a simulation!




All sensitive surfaces are considered to have efficiency = 1
If a track crosses them, then it generates a hit in the detector

Coverage Determination: Lateral View



The lepton side is axially symmetric, lateral and aerial view match


Coverage Determination: Aerial View





The hadron side adapts to the beam pipe asymmetry, the north and south sides are studied separately

The wider cavity of the **south side determines the simplified design ($R_{in} = 110$)**

Impact on Tracking Information




Lepton Side (Lateral View = Aerial View)





Number of sensitive surface crossings are counted for every η interval

Impact on Tracking Information




Hadron Side Lateral View





Number of sensitive surface crossings are counted for every η interval

Impact on Tracking Information




Hadron Side Aerial View North Side




Number of sensitive surface crossings are counted for every η interval

Impact on Tracking Information



Hadron Side Aerial View South Side




Number of sensitive surface crossings are counted for every η interval

Impact on Tracking Information




Comparison – Lepton Side





Loss of tracking information concentrates in $-3.5 < \eta < 3.0$

Sufficient tracking information from SVT available in the same region ($nHit > 2$)

Impact on Tracking Information



Comparison – Hadron Side



Loss of tracking information concentrates in $3.2 > \eta > 3.5$

Sufficient tracking information from SVT available in the same region ($nHit > 2$)

Conclusion



Enough hits (>2) are independently provided by the SVT disks in the region $|\eta|>3$, affected by central cavity optimization

Two extra points from ECT might improve or help conserve tracking performance at $-3.5 < \eta < 3.0$ and $3.2 > \eta > 3.5$



Unless disproven by finer simulations, optimization of the disks' central cavity seems to still be worth the additional workload

~~Thanks for your attention!~~


Off to the CAD for a quick showcase of
the redesign

Backup slides

Recap: ECT and G-RWELL Technology





G-RWELL Technology



ECT Performance Requirements

Spatial resolution	$\leq 150 \mu\text{m}$
Time resolution	$\leq 20 \text{ ns}$
Single layer efficiency	$\geq 97\%$
Material budget (per layer)	$\leq 1\% X_0$



CATHODE

~ 3 mm lightweight support
5 μm copper

DRIFT

6 mm

GEM

5 μm Copper
50 μm Kapton
5 μm Copper

TRANSFER

3 mm \rightarrow 2 mm in the future?


μ -RWELL

10 μm copper
50 μm Kapton
~ 100 nm DLC


R/O

2D strip layout, 600 μm pitch
~ 3 mm lightweight support


ECT Overview





- 4 Disks**
- 16 Quadrant modules**
- 24576 Data channels**



Quadrant Concept



Arrangement of the Quadrants



3 quadrant designs overall:



Electron side

1 design \rightarrow 8 quadrants

Hadron side

2 designs \rightarrow 4 + 4 quadrants


Quadrants **overlap** to achieve total azimuthal coverage*




EAST/HADRON/FORWARD SIDE

*Further details and AA coverage in the backup

Active Area Coverage




WEST/ELECTRON/BACKWARD
SIDE





79,95% envelope coverage
 $-1,72 > \eta > -3,46$

EAST/HADRON/FORWARD
SIDE





78,62% envelope coverage
 $2,01 < \eta < 3,59/3,33$

Complete ETA R/O Sketch



R/O Sketch, Our Input for CERN



Defined ETA PCB shape and mounting interfaces

Convenient form factor for testing, routing/services still constrained by ECT final shape

Towards a Final Design



@ Quadrant level

- **Finalize frames/spacers design**
- Implement gas inlets/outlets + distribution
- Define assembly procedure and jig interfaces
- HV connectors/filter integration
- Implement interconnection interfaces
- FEB integration → FEB supports

Ongoing

@ Disk level

- **Interconnection/support structures**
- **Thermal shielding for BP bakeout**
- Integration within PST
- Installation procedure → mechanical aids
- Mechanical alignment

Coming next

Coming next

@ System level

- Service routing
- Cable supports/cabling schematics

Ongoing and Future R&D Plans



Detector R&D

Engineering Test Article

Objectives:

- Validate **scalability of G-RWELL** technology
- Practice **operation** of a large area detector
- Advance **towards final AA and routing scheme**

Features:

- **Reliable mechanics**
 - FR4 supports for anodes and cathodes
 - Wider, sturdier frames if necessary
- **Recoverable** design:
 - O-ring and screw closure or hybrid solution
 - Glue reservoirs for eventual sealing
- **Semi-final routing** with Hirose connectors
- **Convenient** mounting points and form factor

Mechanics R&D

Mechanical mock-up(s)



Objectives:

- Study **lightweight** mechanical solutions
 - Sandwich-structured composites
- Study **gas tightness** solutions
 - Full epoxy sealing or hybrid solutions
- Study **gas distribution** solutions*
- Study **Vibration resistance** and resonance studies*
- **Practice production techniques**
- **Finalize construction tooling**



Mechanics R&D is now also being conducted on existing large area prototypes
-Lumi upgrade

* unplanned but possible



GEM Sectorization




μ -RWELL Sectorization



Strip Routing Detail




GEM Deflection in Large Area Detectors



TARGET: Drift and Transfer Gap within **10%** of nominal dimensions

- The GEM is glued to the frames
- Tension is applied to the foil before gluing to counteract deflection
- Spacer grids can be introduced to support the foil
- The spacers should not touch the μ -RWELL




Spacer Grid Materials and Dimensioning




All mechanical studies are now being conducted on the existing $\sim 400 \times 460$ AA prototypes (ECT AA = 457x457)

PEEK was the initial candidate for frame production, now **switched to Permglas ME730** (Durostone EPM 203)


The new material **requires PU coating** to avoid particle dispersion (Nuvovern LW)




FEA Results



PEEK



PERMAGLAS




	PEEK	PERMAGLAS
ΔX max	1,242	0,2614
ΔY max	0,9426	0,1981
ΔZ max	0,6683	0,2121

Frames with and without spacers
already in production @ CERN

The gluing tests will inform the design
of the ECT's frames and spacers



Summary of Tested Configurations (PEEK)





Variant	dz	dt	Rods in X	Rods in Y	Mesh size	Max deformation
Baseline	0.2	0.5	3	2	117.43 x 131.13	0.48
Baseline	0.5	0.5	3	2	117.43 x 131.13	0.60
Baseline	1.0	0.5	3	2	117.43 x 131.13	0.93
Thick rods	0.5	1.0	4	3	117.05 x 130.80	0.57
Thin rods	0.5	0.3	4	3	117.58 x 131.25	0.61
Fine mesh	0.2	0.5	4	3	93.84 x 98.20	0.49
Fine mesh	0.5	0.5	4	3	93.84 x 98.20	0.61
Fine mesh	1.0	0.5	4	3	93.84 x 98.20	0.95
Slab	0.2	NA	NA	NA	NA	0.25

The grid either touches the PCB or it is ineffective in containing GEM displacement



GEM Stretching and Gluing Station Pt. 1



GEM Stretching and Gluing Station Pt. 2



GEM Stretching and Gluing Station Pt. 3




**10x Picotronik PS30 digital indicators
(load cell R/O and serial communication)**

**2x DIN rails for Power and GND
distribution + room for feature expansion**


All box parts in Peraluman 5083
+ hard anodization and sealing
for CR compatibility

GEM Stretcher Assembly



AMCO
ATTREZZATURE MECCANICHE E AUTOMAZIONE


Sample preparation



Stretching



BEFORE



12 kg initial tension to have
10 kg after curing


AFTER





Dry Test



- Place frame onto foil
- Center the active area
- Tape in place



- Mark corners and edges
- Place reference silicone pads



Glue Preparation



Glue Deposition, Line Method






The glue is deposited in a thin line in the middle of the allowed region




Needle gauges from 14 (1.6 mm) to 25 (0.254 mm) tested

Various pressures and dispensing times tested

Frame Placement



Test Results




Stretching results are satisfactory

Tension is retained within the frame for both geometries, frame deformation within acceptable range

Glue deposition unsatisfactory on all samples, excessive overflow may require a change of technique

Glue Deposition, Transfer Method





Glue Transfer Technique


Glue is spread on the working surface with a roller and then transferred onto the samples using Nylon film strips

Glue is removed one or more times (also using Nylon strips) to reduce the thickness of the glue layer

Downward force is applied during the curing period with lead weights




Detector Commissioning Pt.1




1

Assembly will be conducted @CERN
→ Easy access to a cleaning facility if
the μ -RWELL is contaminated during
assembly




“Dressing” of the detector
(Installation of filters and connectors)

2



Detector Commissioning Pt. 2



4) Detector Power-on in X-ray flux



→ High rate stability

5) Detector Characterization (Gain Measurement)



→ Determination of operating parameters

6) Search for pathological channels (requires software mapping)

→ R/O production QA



A Cosmic Ray/Test Beam station



Convertible

- For horizontal and vertical operation

Transportable

- For short distances on paved floor
 - **wheeled**
- By forklift and crane for experimental area deployment
 - **Rigid frame, anchor points, longerons and clearance when horizontal**
- By truck over long distances
 - **vibration resistant**

Expandable

- For reuse as more detectors are produced

