

# INTT Publication Plan

RIKEN/RBRC

Itaru Nakagawa

# Proposed plan for INTT Publications

Topics	Target Journal	Leading Author	Timeline	Remaining Issues
Bus Extender ✓ (Electric)	The Japan Institute of Electronics Packaging	Takashi Kondo (TIRI)	2022/May → published Aug. 2022	To be announced from Takashi later
2021 Beam Test ✓	ELPH Ann. Rprt.	Genki/Cheng-Wei/Yuka	2022/Winter	Efficiency (Thick tail by MC, BG contamination)
2021 Beam Test	NIM		2023/Winter	
Bus Extender (Mechanical)	NIM	Takashi	2023/Winter	Final evaluation of the yield rate
INTT Ladder	NIM	Itaru	2023/Winter	Mirco-Coax Conversion Cable/(Commisioning*)
INTT Barrel	NIM	Itaru/Rachid	2024/Summer	Barrel

# Proposed plan for INTT Publications (Update)

Topics	Target Journal	Leading Author	Timeline	Remaining Issues
Bus Extender ✓ (Electric)	The Japan Institute of Electronics Packaging	Takashi Kondo (TIRI)	2022/May → published Aug. 2022	To be announced from Takashi later
2021 Beam Test ✓	ELPH Ann. Rprt.	Genki/Cheng-Wei/Yuka	2022/Winter	ADC distribution, Resolution, Efficiency, cluster size
2021 Beam Test	NIM		2023/Winter	
Bus Extender (Mechanical)	NIM	Takashi	2023/Winter	Final evaluation of the yield rate
<b>INTT Ladder</b>	<b>NIM</b>	<b>Itaru</b>	<b>2025/Winter</b>	<b>Ladder, BEX, CC, ROC</b>
INTT Barrel	NIM	Itaru/Rachid	2024/Summer	Barrel

# Bus Extender Published Paper ✓

Kondo *et al.*: Development of Long and High-Density Flexible Printed Circuits (1/10)

[Technical Paper]

## Development of Long and High-Density Flexible Printed Circuits

Takashi Kondo<sup>1\*</sup>, Kohei Fujiwara<sup>1</sup>, Takashi Hachiya<sup>2,3</sup>, Hikaru Imai<sup>4</sup>, Miu Morita<sup>2</sup>, Itaru Nakagawa<sup>3,4</sup>, Naoyuki Sato<sup>5</sup>, Masato Tsuruta<sup>4</sup>, and Daisuke Yanagawa<sup>5</sup>

<sup>1</sup> Tokyo Metropolitan Industrial Technology Research Institute, 2-4-10, Aomi, Koto, Tokyo 135-0064, Japan

<sup>2</sup> Nara Women's University, Kita-uo-ya-Higashimachi, Nara 630-8506, Japan

<sup>3</sup> RIKEN, 2-1, Hirosawa, Wako, Saitama 351-0198, Japan

<sup>4</sup> Rikkyo University, 3-34-1 Nishi-Ikebukuro, Toshima, Tokyo 171-8501, Japan

<sup>5</sup> Hayashi-Repic Co., Ltd., 1-28-3, Kitaotsuka, Toshima, Tokyo 170-0004, Japan

(Received August 3, 2021; accepted July 7, 2022, published August 4, 2022)

- Only Japanese authors (Students involved in R&D ~2021)
- Focus on electrical property of the bus extender
- Mechanical property such as radiation hardness or mass production technologies are to be discussed in other NIM paper.

### Abstract

The super Pioneering High-Energy Nuclear Interaction eXperiment (sPHENIX), which aims to unravel the mysteries of the creation of the universe, is scheduled to be launched in 2023 at Brookhaven National Laboratory, U.S.A. using the relativistic heavy ion collider. As a typical high-energy particle accelerator-based experiment, the collision area of sPHENIX is to be tightly occupied with various radiation detectors, requiring a minimal special budget to run cables and transmit massive signals generated by these detectors to downstream electronics for data processing located in a remote distance. Accordingly, a long, high signal line-density cable has been developed based on the flexible printed circuit (FPC) technology. FPC comprises multilayers and has extraordinarily long and thin transmission lines. Liquid crystal polymer was employed to suppress losses in transmission lines. Electrical characteristics were evaluated using S-parameters, time domain reflectometry, and eye-diagrams. Furthermore, we have developed manufacturing technology to achieve high-precision microfabrication and improved reliability, which has been demonstrated in peel strength and thermal shock tests. FPC is currently in the mass production phase.

**Keywords:** FPC, LCP, S-parameter, TDR, Eye-diagram, Peel Strength, Through-hole Plating, Radiation Detector Cable

### 1. Introduction

Scheduled to start in 2023, sPHENIX is a novel experiment set up to study a deconfined state of nuclear matter, the quark-gluon plasma (QGP) created in high-energy heavy-ion collisions at the Relativistic Heavy Ion Collider. [1] The intermediate tracker (INTT) is a novel silicon strip detector that can measure more than 1,000 particles generated in collisions. The massive raw data generated from INTT are transmitted at high-speed to downstream electronics for signal-processing through the narrow, curved cable path for longer than 1 m.

Because no commercial cable satisfies the requirement, a novel cable has been developed based on flexible printed circuits (FPC). This technology can simultaneously satisfy high-density signal lines, length, and flexibility.[2–7]

\*: Corresponding author

### 2. Design

#### 2.1 Requirements

Long and high-density signal lines FPCs are required a signal transmission medium for the INTT detector to newly developed for the sPHENIX. Because the transmission lines are required to be long and thin, in the development, it is severely challenging to suppress the signal attenuation and manufacture the fine lines with high accuracy. In addition, high mechanical reliability is required owing to strictly limited access for the maintenance of isolated detector region. The region is to be designated a radiation area during the experiment; hence, detectors are fully operated remotely. Furthermore, the FPC installed in a confined space of the sPHENIX detector complex, and is exposed to a high radiation environment from the collision point and external noise from other signal cables running close to each other. These constraints facilitate the structure of multilayered FPC design.

Transactions of The Japan Institute of Electronics Packaging Vol. 15, 2022




Fig. 4 Simulation results for eye-diagram



(a) Overall view



(b) Connector section

Fig. 5 FPC prototype

line was also confirmed. The gradual increase in the impedance in the time axis direction is a significant characteristic; however, it is known as the effect of the reflected signals that are gradually attenuated by long and thin transmission lines.

To verify that the square-shaped digital signal can be transmitted to a receiver with minimum distortion, the

## Acknowledgement

The authors thank Mr. H. Yanami, Mr. Y. Yanami, Mr. H. Takahashi, and Mr. K. Matsumoto from Print Electronics Laboratory Co., Ltd., and Mr. T. Miyazaki from Taiyo Manufacturing Co., Ltd., for their tremendous support.

# 2021 Beam Test Results ✓

Coarse introduction of INTT →

(ELPH Experiment : #2984)

## Performance evaluation of the Intermediate Tracker for sPHENIX

G. Nukazuka<sup>1</sup>, C.W. Shih<sup>2</sup>, Y. Sugiyama<sup>3</sup>, Y. Akiba<sup>1</sup>, H. En'yo<sup>1,4</sup>, T. Hachiya<sup>3</sup>,  
 S. Hasegawa<sup>5</sup>, M. Hata<sup>3</sup>, H. Imai<sup>4,6</sup>, M. Morita<sup>3</sup>, I. Nakagawa<sup>1,4</sup>,  
 Y. Nakamura<sup>6</sup>, G. Nakano<sup>6</sup>, Y. Namimoto<sup>3</sup>, R. Nouicer<sup>7</sup>, M. Shibata<sup>3</sup>,  
 M. Shimomura<sup>3</sup>, R. Takahama<sup>3</sup>, K. Toho<sup>8</sup>, M. Tsuruta<sup>8</sup>, and M. Watanabe<sup>3</sup>

<sup>1</sup>RIKEN BNL Research Center, Brookhaven National Laboratory, Upton, New York 11973-5000, USA

<sup>2</sup>Department of Physics, and Center of High-energy and High-field Physics, National Central University, Chungli, Taiwan

<sup>3</sup>Nara Women's University, Kita-uoya Nishi-machi Nara 630-8506, Japan

<sup>4</sup>RIKEN Nishina Center for Accelerator-Based Science, Wako, Saitama 351-0198, Japan

<sup>5</sup>Advanced Science Research Center, Japan Atomic Energy Agency, 2-4 Shirakata Shirane, Tokai-mura, Naka-gun, Ibaraki-ken 319-1195, Japan

<sup>6</sup>Physics Department, Rikkyo University, 3-34-1 Nishi-Ikebukuro, Toshima, Tokyo 171-8501, Japan

<sup>7</sup>Brookhaven National Laboratory, Upton, New York 11973

<sup>8</sup>Research Center for Electron Photon Science, Tohoku University, Sendai, 982-0826

Three leading authors: Genki, Cheng-Wei, Yuka for their major contribution to the analysis

## §2. INTT

INTT is a silicon strip barrel detector consisting of two layers of silicon strip sensors surrounding the collision point seven to ten centimeters away (Figure 1). Hits detected by this detector are used not only for interpolation of tracking between MVTX and TPC but also bunch-crossing identification to suppress event-pileup background thanks to the best timing resolution of all tracking detectors in sPHENIX. 24 or 32 INTT ladders form the inner and outer layers. The INTT ladder (Figure 2) consists




Fig.1. A half part of the INTT barrel. The inner and the outer barrels consist of 24 and 32 INTT ladders, respectively. The red box indicates an INTT ladder.




Fig.2. The INTT ladder consists of two types of silicon sensors, FPHX chips, High-Density Interconnect cable, and CFC stave. The sensors are divided into 10 or 16 cells. The silicon cells have 128 strips with 78 μm width and 320 μm thickness. The x-, y-, and z-axes in the test beam experiment are also shown.

## DAC Scan →




Fig.4. The ADC distribution of the eight runs after normalization. The legend indicates the scanning region of the runs.




Fig.5. The energy deposit curve as a function of DAC value. Fitting to the distribution with the sum of a Landau-Gaussian convolution function (dotted blue) and an exponential function (dashed green) is also shown.




Fig.10. The detection efficiency as a function of the track position. (Left) The beam spot is in the middle. (Right) The beam spot aligns with the edge. The error bars indicate the statistic uncertainties.

→ Detection Efficiency  $\approx$  99%

# Ladder NIM Status

## The Performance of sPHENIX Intermediate Silicon Strip Ladder\*

Y. Akiba<sup>a,b</sup>, H. Aso<sup>g,a</sup>, J. T. Bertaux<sup>i,b</sup>, D. Cacace<sup>c</sup>, K. Cheng<sup>d,b</sup>, H. Enyo<sup>a,b</sup>, T. Hachiya<sup>c,b</sup>, S. Hasegawa<sup>f</sup>, M. Hata<sup>c,b</sup>, T. Ichino<sup>g,a</sup>, H. Imagawa<sup>g,a</sup>, H. Imai<sup>g,a,b</sup>, M. Isshiki<sup>c</sup>, Y. Kawashima<sup>g,a</sup>, T. Kondo<sup>b</sup>, C. Kuo<sup>d</sup>, C. Kureha<sup>c</sup>, H.-S. Li<sup>d</sup>, R.-S. Lu<sup>i</sup>, E. Mannel<sup>c</sup>, H. Masuda<sup>g,a</sup>, G. Mitsuka<sup>b</sup>, M. Morita<sup>c,b</sup>, I. Nakagawa<sup>a,b,\*</sup>, Y. Nakamura<sup>g,a</sup>, G. Nakano<sup>g,a</sup>, Y. Namimoto<sup>e,b</sup>, D. Nemoto<sup>g,a</sup>, S. Nishimori<sup>c</sup>, R. Nouicer<sup>c</sup>, G. Nukazuka<sup>b</sup>, R. Pisani<sup>c</sup>, M. Shibata<sup>c,b</sup>, C. Shih<sup>d,b</sup>, K. Shiina<sup>g,a</sup>, M. Shimomura<sup>e</sup>, M. Stojanovic<sup>i,b</sup>, K. Sugino<sup>c</sup>, Y. Sugiyama<sup>c</sup>, A. Suzuki<sup>c,b</sup>, R. Takahama<sup>c,b</sup>, W.-C. Tang<sup>d,b</sup>, T. Todoroki<sup>b</sup>, T. Tsuruta<sup>g,a</sup>, Y. Yamaguchi<sup>b</sup>, M. Watanabe<sup>c,b</sup>, X. Wei<sup>i</sup> and R. Xiao<sup>i</sup>

<sup>a</sup>RIKEN, Nishina Center for Accelerator-Based Science, 2-1 Hirosawa, Wako, 351-0198, Saitama, Japan

<sup>b</sup>RIKEN BNL Research Center, 20 Pennsylvania Avenue, Upton, 11973, NY, U.S.A.

<sup>c</sup>Brookhaven National Laboratory, 20 Pennsylvania Avenue, Upton, 11973, NY, U.S.A.

<sup>d</sup>National Central University, Department of Physics, . . . , Taiwan

<sup>e</sup>Nara Women's University, Department of Mathematical and Physical Sciences, . . . , Japan

<sup>f</sup>Japan Atomic Energy Agency, . . . , Japan

<sup>g</sup>Rikkyo University, Department of Physics, . . . , Japan

<sup>h</sup>Tokyo Metropolitan Industrial Technology Research Institute, . . . , Japan

<sup>i</sup>Purdue University, Department of Physics and Astronomy, . . . , U.S.A.

<sup>j</sup>National Taiwan University, Department of Physics, . . . , U.S.A.

### ARTICLE INFO

#### Keywords:

RHIC  
sPHENIX  
INTT  
Silicon Detector

### ABSTRACT

A new silicon detector has been developed to provide the sPHENIX experiment with precise charged particle tracking for central rapidity. sPHENIX is a new detector at the Relativistic Heavy Ion Collider (RHIC) in the Brookhaven National Laboratory, and will take first physics data in early 2023. The intermediate silicon tracker (INTT) is aimed to be installed in sPHENIX of the Relativistic Heavy Ion Collider (RHIC).

### 1. Introduction

sPHENIX is a new detector at the Relativistic Heavy Ion Collider (RHIC) in the Brookhaven National Laboratory, and will take first physics data in early 2023. The sPHENIX experiment will collect high statistics proton-proton, proton-nucleus and nucleus-nucleus data, enabling state-of-the-art studies of jet modification, upsilon suppression and open heavy flavor production to probe the microscopic nature of the strongly-coupled Quark Gluon Plasma complementary to those measurements from the LHC experiments, and will allow a broad range of cold QCD studies. The sPHENIX detector will provide precision vertexing, tracking and electromagnetic and hadronic calorimetry in the central pseudorapidity region  $|\eta| < 1.1$  with

tracker (INTT) and a time projection chamber (TPC). The calorimeter stack includes a tungsten/scintillating fiber electromagnetic calorimeter (EMCAL) and a steel/scintillator tile hadronic calorimeter (HCAL), divided into inner and outer parts. The inner HCAL sits inside a 1.5 T superconducting solenoid, which was obtained from the decommissioned BaBar detector. In this talk, I will introduce physics goal of the sPHENIX experiment and various detector technologies.

### 2. Detector Overview

The INTT consists of 56 ladders, it is responsible for measuring in the position and the timing of charged particles.

- Author list: INTT collaboration up to ~2022. (To be updated to ~2023 list?).
- Scope of the Paper
  - Design of the ladder.
  - Excluding the beam test performance.
  - Barrel is not included. No 1008 commissioning neither.
- Under development by Itaru in overleaf

<https://www.overleaf.com/project/63680cb8918e6f1961ae3972>

# Ladder NIM Status

## **Contents**

- Introduction
- HPK Silicon Sensor
- FPHX Chip (short ver.)
- HDI
- Carbon Fiber Stave
- Bus Extender
- Conversion Cable
- ~~ROC + Felix~~

## **Focus**

- Dimensions
- Channels
- Structures
- Electric Properties

# dN/deta Physics Paper

$$\frac{dN_{particle}}{d\eta} = \frac{1}{N_{evt}} \cdot \frac{1}{\Delta\eta} \cdot N_{particle}(\eta)$$

$$N_{particle}(\eta) = \frac{(N_{hits} - N_{bg})}{\epsilon_{acc} \cdot \epsilon_{eff}} \text{ for each } \eta \text{ range}$$

$\epsilon_{eff}$  : Ideally to be evaluated by 1008 barrel from the commissioning. This is not easy with only 2 INTT layers. One idea is to quote 99.6% from published 2021 beam test NIM.

→NIM should be published before dN/dη paper

## Signal extraction from data

$$(N_{hits} - N_{bg}) \cong N_{hits} \cdot f_{bkg}$$

### Data analysis

- $N_{hits}$  = *Ntracks or Nhits for each η bin*
  - $\eta$  = *track/cluster position from (X-Y-Z)-vertex*
- $N_{bg}$  = *estimate BG using data and BG*
  - Random BG and BG from decay (long-lived)
  - if relative fraction of S/N is known, It is OK
- **Data QA is necessary**

## Detector acceptance and efficiency

$$\epsilon_{acc} \cdot \epsilon_{eff}$$

### MC (SIM)

- Can be determined with hot&dead and alignment.
- Occupancy effect (by multiplicity) needs to be studied with centrality
  - Good to check it by data



# Scope for the Barrel NIM

## Contents

- Introduction
- Barrel
- LV/Bias power system
- Cooling System and Performance
- ROC
- Felix
- RC-DAQ

## Beam Commissioning

- # of live channels
- Timing resolution
- DAC Scan
- Signal to noise ratio
- Efficiency
- Clustering
- Tracklet
- Z-vertex reconstruction performance

} dN/d $\eta$  paper?