


# Outer MPGD Detector Cooling


Seungjoon Lee  
BOT Engineer

02/19/2026


Electron-Ion Collider




# MPGD-BOT module: FEB with cooling



MPGD Barrel Outer Tracker (MPGD-BOT)



FEBs




cooling tubing for the 2<sup>nd</sup> module behind

Mounting Frame

FEB

Heatsink with tubing

Service Area




FEB without Heatsink

Communication Board

SALSA Board


Power Board



Cooling tubing

FEB with Aluminum Heatsink

# MPGD-BOT module: FEB cooling design



## Expected Cooling Parameters

Total power:  $112\text{W} = 16\text{W} \times 7 \text{ FEB}$


Flow rate:  $1.6 \text{ L/min}$

Flow speed:  $\sim 1.5 \text{ m/s}$  (OK for 5 mm ID pipe)

$T_{\text{in}} = 22 \text{ }^\circ\text{C}$ ,  $dT < 1 \text{ }^\circ\text{C}$


*Requires more dedicated thermal simulation*

# Heatsink Model for Simulation



- Stainless Steel (304) Pipe embedded Aluminum Heatsink. (5 mm OD)
- 304 Stainless steel ( $\sim 16.5$  W/mK)
- 6063 Aluminum (200 W/mk)
  
- Why Stainless steel? – 0.25 mm wall thickness. (0.5 mm for copper for similar sized pipe)
- If SS conductivity has issue, copper or brass can be an option.

# Components



| Number | Name      | Power (mW) |
|--------|-----------|------------|
| 1      | DC/DC     | 4400       |
| 2      | SALSA1    | 1800       |
| 3      | SALSA2    | 1800       |
| 4      | SALSA3    | 1800       |
| 5      | SALSA4    | 1800       |
| 6      | LDO_S1    | 450        |
| 7      | LDO_S2    | 450        |
| 8      | LDO_S3    | 450        |
| 9      | LDO_S4    | 450        |
| 10     | LDO_lpGBT | 156        |
| 11     | LDO_VTRX  | 875        |
| 12     | lpGBT     | 600        |
| 13     | VTRX      | 175        |
|        | TOTAL     | 15,206     |

# Detector – Heat Load

## Temperature rise 0.5 C

|             |         |        |
|-------------|---------|--------|
| FEB         | 15.5    | W      |
| with margin | 16      | W      |
| dT          | 0.5     | C      |
| Cp          | 4181    | J/kg C |
| m           | 0.00741 | kg/s   |
| m           | 0.00741 | l/s    |
| m           | 7.41    | ml/s   |

|          |       |         |
|----------|-------|---------|
| Velocity | 0.467 | m/s     |
| Re       | 2198  | Laminar |

|                         |      |   |
|-------------------------|------|---|
| Inlet water Temperature | 22   | C |
| Ambient Temperature     | 23.3 | C |

## Temperature rise 2 C

|             |         |        |
|-------------|---------|--------|
| FEB         | 15.5    | W      |
| with margin | 16      | W      |
| dT          | 2       | C      |
| Cp          | 4181    | J/kg C |
| m           | 0.00185 | kg/s   |
| m           | 0.00185 | l/s    |
| m           | 1.853   | ml/s   |


|          |        |         |
|----------|--------|---------|
| Velocity | 0.1168 | m/s     |
| Re       | 549.53 | Laminar |

# Detector – Heat Load

| Component | Power<br>mW | Power<br>W | Area<br>mm <sup>2</sup> | Area<br>m <sup>2</sup> | Heat Flux<br>W/m <sup>2</sup> |
|-----------|-------------|------------|-------------------------|------------------------|-------------------------------|
| DC/DC     | 4,400       | 4.4        | 200                     | 0.0002                 | 22,000                        |
| SALSA     | 1,800       | 1.8        | 100                     | 0.0001                 | 18,000                        |
| SALSA     | 1,800       | 1.8        | 100                     | 0.0001                 | 18,000                        |
| SALSA     | 1,800       | 1.8        | 100                     | 0.0001                 | 18,000                        |
| SALSA     | 1,800       | 1.8        | 100                     | 0.0001                 | 18,000                        |
| LDO       | 450         | 0.45       | 50                      | 0.00005                | 9,000                         |
| LDO       | 450         | 0.45       | 50                      | 0.00005                | 9,000                         |
| LDO       | 450         | 0.45       | 50                      | 0.00005                | 9,000                         |
| LDO       | 450         | 0.45       | 50                      | 0.00005                | 9,000                         |
| LDO IpGBT | 156         | 0.156      | 50                      | 0.00005                | 3,120                         |
| LDO VTRX  | 875         | 0.875      | 50                      | 0.00005                | 17,500                        |
| IpGBT     | 600         | 0.6        | 100                     | 0.0001                 | 6,000                         |
| VTRX      | 175         | 0.175      | 100                     | 0.0001                 | 1,750                         |
|           |             |            |                         |                        |                               |
|           | 15206       | 15.206     |                         |                        |                               |



## Components Heat load data

# Results – 0.5C temperature rise (Girish, BNL)





Temperature distribution


Static Temperature [C]



Static Temperature [C]



# Results – 2C temperature rise (Girish, BNL)



Temperature distribution

# Future Plan

---

- Working with Girish (BNL) for simulation of various scenarios
- Including other materials (thermal pad, thermal epoxy)
- Material (Stainless steel, Copper, Brass)
- Heatsink Insulation (prevent ambient heating)
- Flow rate
- Turbulator (in case we need)
  
- Build a baseline simulation package  
=> quickly adapt realistic parameter/requirement from SALSA development
  
- Key parameter for simulation: SALSA power consumption + SALSA operation temperature

# Full Setup



- Total 7 Heatsinks with single SS pipe (+U pipe)
- Working on full scale simulation (not done yet)
- Expecting even cooling for all 7 FEBs