




# BNL and ePIC Network Overview

Mark Lukasczyk  
Network Engineering

2/26/2025



# BNL High Throughput Science Network (HTSN)




# Total Traffic – Past Year

## BNL Internet/WAN Bandwidth Utilization




	Value
Total Outbound	202 PB
Total Inbound	137 PB

## BNL Network Perimeter Bandwidth Utilization





	Value	Percent
LHCONE_Outbound	85.8 PB	25%
LHCOPN_Outbound	67.9 PB	20%
LHCOPN_Inbound	63.8 PB	19%
LHCONE_Inbound	48.3 PB	14%
ESNETv6_Outbound	25.5 PB	8%
ESNETv4_Outbound	23.2 PB	7%
ESNETv6_Inbound	16.7 PB	5%
ESNETv4_Inbound	8.21 PB	2%


# READ operations from the dCache Storage Elements over the WAN reach nearly 800 Gb/s




Name	Mean	Min	Max	Last
LHCOPN_Inbound	1.17 Gb/s	45.8 Mb/s	5.51 Gb/s	417 Mb/s
LHCOPN_Outbound	80.2 Gb/s	760 Mb/s	275 Gb/s	2.00 Gb/s
LHCONE_Inbound	14.3 Gb/s	278 Mb/s	63.5 Gb/s	1.14 Gb/s
LHCONE_Outbound	176 Gb/s	1.61 Gb/s	463 Gb/s	27.6 Gb/s
ESNETv4_Inbound	6.10 Gb/s	2.10 Gb/s	12.6 Gb/s	4.35 Gb/s
ESNETv4_Outbound	42.7 Gb/s	905 Mb/s	69.8 Gb/s	10.1 Gb/s
ESNETv6_Inbound	12.7 Gb/s	229 Mb/s	66.8 Gb/s	339 Mb/s
ESNETv6_Outbound	64.0 Gb/s	205 Mb/s	123 Gb/s	14.9 Gb/s




# BNL High Throughput Science Network (HTSN) with ePIC



# HTSN/SDCC Network Infrastructure



# Fiber Path Between IP6 (1006) and SCDF (725)



- Consists of a series of single multi-fiber cable runs, shown in yellow, connecting buildings 515, 911, 1005, 1006.
- The cables are terminated in patch panels in each of the buildings, and patch cables are used to connect the fibers between the cables.
- A break in any one of these cables would result in loss of connectivity from ePIC to the data center.
- Currently, approximately two-thirds of the fiber capacity between buildings 515 and 1005 has been utilized in support of RHIC.

# Questions