



A cosmic rays tracking system for the stability monitoring of historical buildings

D. Pagano¹, G. Bonomi¹, M. Caccia², A. Donzella¹, V. Villa¹, A. Zenoni¹

¹University of Brescia & INFN Pavia

²University of Insubria & INFN Milano

D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

Motivations



D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

Motivations



D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings



D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

Atlanta 2019

Motivations



D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

Atlanta 2019



Stability monitoring of buildings: the "Palazzo della Loggia" case

D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings



• Formentone: first proposal (wooden model)

The "Palazzo della Loggia" case



• Formentone: first proposal (wooden model)



The "Palazzo della Loggia" case



• Formentone: first proposal (wooden model)



• Original dome destroyed by fire and replaced by a *temporary* roof



• Formentone: first proposal (wooden model)



- Original dome destroyed by fire and replaced by a *temporary* roof
- Temporary roof replaced by an attic

The "Palazzo della Loggia" case



• Formentone: first proposal (wooden mode



Original dome destroyed by fire and replace

• Temporary roof replaced by an attic



D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

Atlanta 2019



• Formentone: first proposal (wooden model)



- Original dome destroyed by fire and replaced by a *temporary* roof
- Temporary roof replaced by an attic
- A new dome, based on the original project, replaced the attic

D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

• Since its reconstruction, the dome exhibited a progressive deformation

The "Palazzo della Loggia" case

• Since its reconstruction, the dome exhibited a progressive deformation



The "Palazzo della Loggia" case

• Since its reconstruction, the dome exhibited a progressive deformation



- Since its reconstruction, the dome exhibited a progressive deformation
- For this reason a systematic campaign of monitoring of the dome was performed by using (invasive) extensometers
- Pairs of wires (Ø = 2 mm): invar (nikel-iron alloy) and steel
- Mechanical stabilization of the tension





A. Bellini et al., "Il Palazzo della Loggia di Brescia - Indagini e progetti per la conservazione", Starrylink editrice, 2007

A cosmic rays tracking system for the stability monitoring of historical buildings

The "Palazzo della Loggia" case

- Data taking lasted for more than 10 years
- A deformation of ~1 mm/year was measured
- Stable load-bearing walls: only the dome is affected





A cosmic rays tracking system for the stability monitoring of historical buildings

Stability monitoring of buildings: state of the art

• Stability monitoring for historical buildings is fundamental and their structural vulnerability is also recognized at regulatory level



Stability monitoring of buildings: state of the art

• Stability monitoring for historical buildings is fundamental and their structural vulnerability is also recognized at regulatory level



 Current techniques include the use of mechanical or optical systems, vision-based methods, sensors such as accelerometers, etc...

D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

Stability monitoring of buildings: state of the art

P25A suspension bridge, Lisbon (Portugal)



L. Lages Martins, J. M. Rebordão and A. Silva Ribeiro Journal of Physics: Conference Series 588 (2015) 012004









D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

Atlanta 2019

Monitoring system consisting of accelerometers, thermometers and **fiber optic sensors**

2 μm RMS

Atlanta 2019



Torre Aquila, Trento, Italy



D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

- Current techniques (some of them shown in the previous slides) have some drawbacks:
 - Some are not suitable for continuous monitoring
 - Some are very specific (type of buildings, type of deformation, ...)
 - Many are quite **invasive**
- For historical building strong constraints on invasiveness apply

- Current techniques (some of them shown in the previous slides) have some drawbacks:
 - Some are not suitable for continuous monitoring.
 Sor
 Mar
 For hist

- Current techniques (some of them shown in the previous slides) have some drawbacks:
 - Some are not suitable for continuous nonitoring
 Sor
 Mat
 For hist

- Current techniques (some of them shown in the previous slides) have some drawbacks:
 - Some are not suitable for continuous monitoring
 - Some are very specific (type of buildings, type of deformation, ...)
 - Many are quite **invasive**
- For historical buildings strong constraints on invasiveness apply
- Therefore we investigated the possibility of a monitoring system based on the reconstruction of cosmic muons by means of *compact* detectors
 - Deformation of historical buildings occur over a *long* period of time, so the limited rate of cosmic muons could not be an issue

D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

- buse of a free natural source of radiation
- muons are highly penetrating: walls and floors are easily traversed
- In the second second
- 👍 limited invasiveness
- possibility to design a global monitoring system
- fixed rate of cosmic muons: (relatively) long data taking
- For all these reasons, the possibility of using cosmic muons for the stability monitoring of historical buildings has been investigated
- Palazzo della Loggia in Brescia has been chosen as a benchmark case

D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

IOP Publishing

Meas. Sci. Technol. 30 (2019) 045901 (9pp)

Measurement Science and Technology

https://doi.org/10.1088/1361-6501/ab00d7

Cosmic ray tracking to monitor the stability of historical buildings: a feasibility study

G Bonomi^{1,2,5}, M Caccia^{3,4}, A Donzella^{1,2}, D Pagano^{1,2}, V Villa¹ and A Zenoni^{1,2}

¹ Department of Mechanical and Industrial Engineering, University of Brescia, via Branze 38, 25123
 ² INFN Pavia, via Bassi 6, 27100 Pavia, Italy
 ³ Department of Science and High Technology, University of Insubria, Via Valleggio 11, 22100 Como, Italy

⁴ INFN Milano, via Celoria 16, 20133 Milano, Italy

E-mail: germano.bonomi@cern.ch

Received 17 July 2018, revised 29 November 2018 Accepted for publication 22 January 2019 Published 1 March 2019



Abstract

A cosmic ray muon detection system is proposed for stability monitoring in the field of civil engineering, in particular for the static monitoring of historical buildings, where conservation constraints are severe and the time evolution of the deformation phenomena under study may be of the order of months or years. The stability monitoring of the wooden vaulted roof of the *Palazzo della Loggia*, located in the town of Brescia, Italy, has been considered as a case study. The feasibility, as well as the performance and limitations of a stability monitoring system based on cosmic ray tracking have been studied by Monte Carlo simulations. A study of possible systematic uncertainties is presented along with a realistic design for the construction of a measurement system prototype.

D. Pagano



Proposed detector

- double layers of scintillating (3 x 3) mm² fibers
- fibers coupled to SiPMs
 - cheap
 - low voltage operation
 - good spatial and time resolution

D. Pagano

400 mm

(3 x 3 x 400) mm³

400 mm

A cosmic rays tracking system for the stability monitoring of historical buildings

- MC simulations performed in three different configurations:
 - 1: $\Delta z = 350 \ cm$
 - **2**: Δ*z* = 880 *cm*
 - **3**: $\Delta z = 1300 \ cm$
- No visibility between the detectors:
 - 15 cm of concrete ←
- Realistic cosmic muon generator
 based on experimental data

Bonechi et al. (2005) Proc. 29th Int. Cosmic Ray Conf. vol 9 p 283

Systematic uncertainties taken into account (details in the next slides)



D. Pagano

Reconstruction algorithms: geometrical approach

- x z and y z views independently reconstructed (x z case here)
- For perfectly aligned geometry expected values $E[x'_h x'_l] = 0$ and $E[\theta_h \theta_l] = 0$
- $x'_h x'_l$ and $\theta_h \theta_l$ depend on the parameters of interest x_d and θ_d
- Estimates \hat{x}_d and $\hat{\theta}_d$ from a χ^2 minimization



$$\chi^{2} = \sum_{i} \left[\frac{(x_{h,i}' - x_{l,i}')^{2}}{(\sigma_{x_{h}',i}^{2} + \sigma_{x_{l}',i}^{2})^{2}} + \frac{(\theta_{h,i} - \theta_{l,i})^{2}}{(\sigma_{\theta_{h,i},i}^{2} + \sigma_{\theta_{l,i},i}^{2})^{2}} \right]$$

• Index *i* runs over the reconstruted muons in the data sample

D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

A possible improvement

- Coulomb scattering distribution well represented by the theory of Molière
- Roughly Gaussian (small deflection angles)
- By defining $\theta_0 = \theta_{plane}^{rms} = \frac{1}{\sqrt{2}} \theta_{space}^{rms}$

$$x/2$$

 y_{plane}
 y_{plane}
 y_{plane}
 θ_{plane}

Highland parametrization $\theta_0 \simeq \frac{13.6 \text{ MeV}}{\beta cp} z \left[\frac{x}{X_0} \left[1 + 0.038 \ln\left(\frac{x}{X_0}\right) \right] \right] \qquad \theta_0 \simeq \frac{\chi_c^2}{1 + F^2} \left[\frac{1 + v}{v} \ln(1 + v) - 1 \right]$

Lynch-Dahl parametrization

- Scattering "shift": $y_0 = y_{plane}^{rms} \cong \frac{1}{\sqrt{3}} x \theta_0$
- We investigated the possibility of using this information to improve the reconstruction performance

D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

A possible improvement



Data PLB94,35(2004)

100.0

50.0

0.6





D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

• Estimates \hat{x}_d and $\hat{\theta}_d$ can be obtained by maximazing the likelihood

$$L(x_{d}, \theta_{d}) = \prod_{i} L_{\theta_{0}}(\theta_{0,i} | \theta_{h,i}, x'_{h,i}, x_{d}, \theta_{d}) \cdot L_{y_{0}}(y_{0,i} | \theta_{h,i}, x'_{h,i}, x_{d}, \theta_{d})$$



• Better performance in complex configurations with multiple passive materials, etc... but only marginal improvements for our benchmark case

D. Pagano

• For a given number of muons, the uncertainties on \hat{x}_d and $\hat{\theta}_d$ were estimated from samples of \hat{x}_d and $\hat{\theta}_d$ obtained from a large number of different MC generations

Results



D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

Results

• Systematic uncertainties related to geometrical tollerances in the detectors and to their relative positioning were taken into account



D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings



Design and development of a small-scale prototype

D. Pagano

A cosmic rays tracking system for the stability monitoring of historical buildings

The small-scale detector prototype .

- As a proof of principle a small-scale detection system, consisting of two telescopes with three detecting layers each, was designed and created
- Layers composed by 3×3 mm² scintillating fibers (BCF-10 from Saint-Gobain)
- ABS mechanical supports created with a 3D printer









Scintillating fibers coupled to SiPMs (SiPM3S-P from AdvanSiD)





Effective Active Area	3×3	mm^2
Cell Size	50×50	μm^2
Cells number	3600	—
Spectral response range	$350 \div 900$	nm
Peak sensitivity wavelength	390	nm
Photon Detection Efficiency	33	%
Breakdown Voltage	27 ± 2	V
Dark Count	$100 \times 10^3 \div 300 \times 10^3$	Cps/mm^2
Gain	4×10^{6}	_
Breakdown Voltage temperature sensitivity	26	$mV/^{\circ}C$

The small-scale detector prototype

- Signals from SiPMs amplified with a (custom made*) three stages amplification module
- All SiPMs were fully characterized and dependences of V_{bd}, dark counts, etc... on the temperature were studied

25,0

25,5

 $V_{hd} = 24,37 \pm 0,02 V$

23,5

23,0

24,0

24,5



COMPUTER

Dark Current [nA]

10²

10¹

100

22,5

27,5

28,0

Reverse Bias [V]

28,5

26.5

24,3

27,0

26,5

26,0

24,4

The small-scale detector prototype .



24,2

15,0

20,0

25,0

30,0

40,0

45,0

50,0

Temperature [°C]

35,0

- 24,2

55,0

The experimental setup







A cosmic rays tracking system for the stability monitoring of historical buildings



Results



- We presented a technique and a suitable detector for the stability monitoring of (historical) buildings, using cosmic ray muons
- The technique was applied to a realistic scenario, using the "Palazzo della Loggia" in Brescia a case study
- Three different geometrical configurations (from $\Delta z = 350$ to 1300 cm) were considered
- MC results, including systematic uncertainties, showed that resolutions of 1 mm (or better) could be achieved with data from few days
- As a proof of principle, we also developed a small-scale detector prototype based on the same technology of the proposed detector
- Performance was compared to MC simulations with a good agreement