

Boundary conditions on the EIC detector design

Alexander Kiselev (with a lot of recent input from Walt Akers)

EICUG “Berkeley” Zoom meeting November 19, 2020

Topics

- Space limitations
- Experimental hall(s)
- Material budget considerations
- IR vacuum chamber
- Central detector solenoid
- Detector maintenance

Space limitations


- Machine
 - ▶ L^* should be small (luminosity)
 - ▶ Crossing angle is a must (luminosity)
 - ▶ Beam pipe diameter at the IP is substantial (synchrotron fan)
 - ▶ Beam pipe ~ 20 mrad opening angle in the hadron-going direction is required
- Experimental hall constraints (EIC is **not** a green field installation)
- Subsystem length vs performance
 - ▶ Hadronic calorimetry: how long is long enough?

η	$\sim[-4 .. -1]$	$\sim[-1 .. 1]$	$\sim[1 .. 4]$
ZEUS HCal (DU part)	$\sim 4 \lambda_1$	$\sim 5 \lambda_1$	$\sim 7 \lambda_1$
EIC HCal	$\sim 5 \lambda_1$	$\sim 5 \lambda_1$	$\sim 6-7 \lambda_1$

- ▶ RICH: 100cm? 140cm (presently allocated)? 160cm (most of the studies to date)?
- ▶ Forward / backward silicon tracker: well, the more the better

EIC reference detector in RHIC IP6

“Realistic” detector space allocations (but no support structures, etc.)



Beam pipe footprint is to scale in this picture, but are we really getting down to +/- 4 in η ?

$ \eta = 3.00$	$ \eta = 3.50$	$ \eta = 4.00$	$ \eta \sim 4.38$	$ \eta = 4.50$
~ 99.5 mrad	~ 60.4 mrad	~ 36.6 mrad	25.0 mrad	~ 22.2 mrad


-4 < η < 4 acceptance?

- Fiducial volume cuts
 - ▶ e/m calorimetry: typically one tower away from the edge for “nominal performance”
 - ▶ Hadronic calorimetry: one interaction length away from the edge (just veto otherwise?)
 - ▶ Trackers: outer frames (centimeters, small?; well, 1 cm at 2 meters is a loss of 5 mrad)
 - ▶ High-momentum RICH: gas vessel, photon detection inefficiency at high η
- Azimuthal asymmetry in acceptance and performance
 - ▶ Electron-going endcap: crossing angle and synchrotron fan in horizontal plane
 - ▶ Hadron-going endcap: strong asymmetry in B^*dl integral


Assume 5 ITS2-like stations, 3T field and 1m lever arm

Forward silicon tracker momentum resolution study

by Rey Cruz-Torres



Solenoid magnet considerations



Ignore the actual layout (older toy model picture)

Want to maximize $B \cdot dl$ integral for the silicon tracker at high $|\eta|$ Want projective field in the RICH at medium $|\eta|$

- These two requirements are somewhat in a contradiction in the hadron-going endcap, especially if the additional high-resolution tracking stations behind the RICH are desirable
- Bore diameter can hardly exceed ~4m (otherwise the barrel detector won't fit through the IP6 exp. hall door); currently considered: up to 3.4 m green field design, ~2.8 m BaBar magnet
- Solenoid flux return scheme strongly depends on the HCal absorber choice (magnetic or not)


Solenoid magnet considerations

- 1.4T (BaBar), 2.0T, 3.0T?
 - High $|\eta|$ tracking
 - Low P_T (curling) tracks at central rapidities
 - Photo-sensors in high magnetic field; field orientation
- Comparison to HERA collider experiments:

	Central field	Bore diameter	Barrel EmCal	Barrel HCal
H1	1.15 T	~518 cm	inside	inside
ZEUS	1.43 T	~172 cm	outside	outside
EIC	up to 3.0 T	up to 340 cm	inside	outside


Material budget

- Low material budget is a must for EIC
 - ▶ Minimize bremsstrahlung and conversions for primary particles
 - ▶ Improve tracking performance at large $|\eta|$ by minimizing multiple Coulomb scattering
 - ▶ Minimize the dead material in front of the high resolution e/m calorimeters





So: ~5% of tracker material in the whole angular range up to $|\eta| \sim 3.5$? **NO**




Material budget



New Cage/TPC brackets fit check and positions survey →




Clear acceptance is never the full story ...



Beam pipe (March 2020 design) material scan


Electron endcap side
Material in acceptance, [%]



+/- 60 mrad

- ❑ Endcap pipe rectangular part: aluminum (layout needs improvement)
- ❑ Full range: $-4.5 < \eta < -3.5$
- ❑ White circle: $\eta = -4.0$



Hadron endcap side
Material in acceptance, [%]



+/- 60 mrad

- ❑ Endcap pipe conical part: aluminum (layout needs improvement)
- ❑ Full range: $3.5 < \eta < 4.5$
- ❑ White circle: $\eta = 4.0$


- ❑ Central area (around IP): (ok) beryllium beampipe with the outer diameter 63.5 mm
- ❑ Few % radiation length material thickness in the most part of the required angular range



Top view


The new beam pipe design exists (longer Be section; optimized flange locations)

B0 spectrometer in the far forward region



Detector	Angular Acceptance
ZDC @ ~30m	$\theta < 5.5$ mrad
Roman Pots	$0.0^* < \theta < 5.0$ mrad
Off-Momentum Detectors	$0.0 < \theta < 5.0$ mrad
B0 Sensors	$5.5 < \theta < 20.0$ mrad

- B0: 20 mrad or less? or more?
 - ▶ Substantial B0 acceptance is needed for exclusive physics at small hadron beam energy
 - ▶ There will be neither PID nor calorimetry in this acceptance



B0 Silicon Detector


EIC detector in RHIC IP6

- “Large” exp. hall:
 - ▶ Place for rolled-out endcap halves
 - ▶ But very little space along the beam line (which suggests no significant assembly work in this area)

- Small door to the installation area:
 - ▶ May need to split off the endcap(s)
 - ▶ Creative cryo connection required

- Low doorway
 - ▶ Electronics trailer can only be attached next to the detector

- Crane capacity:
 - ▶ 20 tons in the installation area
 - ▶ 40 tons in the assembly area




Door width	823 cm
Door height	823 cm

Maintenance modes & access options

- Short access (hours) – no major disassembly actions
 - ▶ Electronics trailer
 - ▶ HCal frontend electronics
 - ▶ Cryocan
- Longer access (days to weeks) – endcaps rolled out in halves
 - ▶ EmCal frontend electronics
 - ▶ B0 magnet detectors (silicon tracker and EmCal)
 - ▶ Outer part of the central detector (planar trackers, perhaps the gaseous RICH electronics, perhaps DIRC electronics)
- Regular maintenance (months) – barrel detector moved to the assembly hall
 - ▶ The only option to access the central tracker ...
 - ▶ ... and the forward / vertex / backward silicon trackers


Detector assembly in IP6



- Outer detectors (barrel hadronic calorimeter, cryostat) will be assembled in a “usual” way using crane (no clam shell configuration, as seen now)
- Inner detector insertion will require diverse tooling
- Beam pipe piece assembled together with the silicon vertex detector


IP6: detector in the “longer access” maintenance

Somewhat outdated picture with the cryocan mounted on the detector



- Endcap(s) assembled in the experimental area once and stay there

EIC detector in RHIC IP8




DIMENSIONS FOR IP-8 AND THE ASSEMBLY HALL

Door width	927 cm
Door height	1017 cm

- High enough doorway
 - ▶ Electronics trailer can be installed on top of the detector
- Rails will need to be moved

- Small exp. hall:
 - ▶ No space for either assembly work or detached endcap(s) ...
 - ▶ ... however the detector will likely fit through the door
- “Short” assembly hall
 - ▶ Either expand the area (or use a turntable?)




The takeaway message

- There are several “external” constraints on the central detector design
- They should better be observed when doing physics studies ...
- ... and be realistically accounted in the simulations, as well as in the overall detector design

- Integration work is ongoing

Backup

EIC Interaction Region layout



- ❑ ~9 m around the IP is reserved for the *central* detector
- ❑ But the *far forward* and *far backward* detector components are distributed along the beam line within ± 35 m
- ❑ Very important to keep full detector integration in sync with the accelerator design from the early stages on